

VICTORBILT TECHNICAL BULLETIN

APRIL 2016—EXTERIOR DOOR (WOOD, FIBERGLASS, STEEL) OPENINGS CHART

Unit Size	Rough Stud Opening	Outside Jamb to Outside Jamb	Outside BMC to Outside BMC	Inside Jamb to Inside Jamb
Widths:	+2-1/2"	+1-1/2"	+4"	Door Beveled 3/16"
2-8	2-10 1/2 (2 1/2")	2-9 1/2 (1 1/2")	3-0 (4")	2-8
3-0	3-2 1/2	3-1 1/2	3-4	3-0
4-0 Double	4-3	4-2	4-4 1/2	4-0 1/2
5-0 Double	5-3	5-2	5-4 1/2	5-0 1/2
5-4 Double	5-7	5-6	5-8 1/2	5-4 1/2
6-0 Double	6-3	6-2	6-4 1/2	6-0 1/2
1-0x3-0	4-4	4-3	4-5 1/2	4-1 1/2
1-0x3-0x1/0	5-5 1/2	5-4 1/2	5-7	5-3
Center Hinged Patio Units				
5-0	5-3 13/16	5-2 13/16	5-5 5/16	5-1 5/16
5-4	5-7 13/16	5-6 13/16	5-9 5/16	5-5 5/16
6-0	6-3 13/16	6-2 13/16	6-5 5/16	6-1 5/16
9-0	9-5 1/8	9-4 1/8	9-6 5/8	9-2 5/8
8-0	8-5 1/8	8-4 1/8	8-6 5/8	8-2 5/8
7-6	7-11 1/8	7-10 1/8	8-0 5/8	7-8 5/8
Heights:	+ 3-1/4"	+2-3/4"	+4"	
6-8 (6-7)	6-10 1/4 (3 1/4")	6-9 3/4 (2 3/4")	6-11 (4")	
7-0 (6-11)	7-2 1/4	7-1 3/4	7-3	
8-0 (7-11)	8-2 1/4	8-1 3/4	8-3	
AD & RD	Add 1" but VERIFY WITH DSL			
All Transoms	Add Door RO Height to Transom Size + 1 1/2"			
1-0 Elliptical	$6-10\frac{1}{4}+1-0+1\frac{1}{2}'' = 95\frac{3}{4}''$	95 1/4"	96 1/2"	Example
Handicap Sill (HC)	Deduct 1"	Deduct 1"	Deduct 3/4"	
Outswing Std.	Deduct 5/8"	Deduct 5/8"	Deduct 3/8"	
Outswing HC	Deduct 1"	Deduct 1"	Deduct 1"	