

ACCESS DOORS—INTERIOR

- R-5 THERMAL VALUE
- 1-3/4" THICK FIBERGLASS / POLYURETHANE CORE
- 4-9/16—6-9/16 PRIMED OR COMPOSITE JAMBS
- WEATHERSTRIPPED 4 SIDES
- OPTION FOR ADA, OR REGULAR DOOR SILLS
- PREPPED FOR 2-1/8 CYLINDRICAL BORE
- DEAD BOLT OPTION
- 3 HINGES > 5' > 2 HINGES
- CUSTOM AVAILABLE 1-0 TO 3-6 WIDE; 2-0 TO 6-6 HEIGHT



PREHUNG DOOR SIZES—ROUGH OPENING

20" X 38"	20" X 50"	20" X 63"
22" X 38"	22" X 50"	22" X 63"
24" X 38"	24" X 50"	24" X 63"



ACCESS DOORS—EXTERIOR/CRAWL SPACE

- SINGLE PIECE PVC FOR LESS EXPENSIVE OPTION (SHOWN)
- COMPOSITE JAMBS
- WITH OR WITHOUT WEATHERSTRIP
- CARRIAGE BOLT / LIFT OUT DOORS
- CYLINDRICAL BORE OPTION
- CUSTOM SIZES—GIVE US YOUR MASONRY / STUD OPENING

