

VICTORBILT TECHNICAL BULLETIN—EXTERIOR OPENINGS

	Between Frame / Stud	Between Sill / Floor	Between Head Jamb / Header	
	½" each side	0"	½"	
Unit Size	Rough Stud Opening	Outside Jamb to Outside Jamb	Outside BMC to Outside BMC	Inside Jamb to Inside Jamb
Call Size Widths:	(+2-1/2")	(+1-1/2")	(+4")	Door Beveled 3/16"
2-8	2-10 ½	2-9 ½	3-0 (+1/2" for OS)	2-8
3-0	3-2 ½	3-1 ½	3-4 (+1/2" for OS)	3-0
For Doubles:	(+3")	(+2")	(+4-1/2")	
4-0 Double	4-3	4-2	4-4 ½ (+1/2" for OS)	4-0 ½
5-0 Double	5-3	5-2	5-4 ½ (+1/2" for OS)	5-0 ½
5-4 Double	5-7	5-6	5-8 ½ (+1/2" for OS)	5-4 ½
6-0 Double	6-3	6-2	6-4 ½ (+1/2" for OS)	6-0 ½
5-0 SFG Retro Double	5-0 1-4	4-11 1/4	5-1 3/4 (+1/2" for OS)	4-9 3/4
6-0 SFG Retro Double	6-0 1/4	5-11 1/4	6-1 3/4 (+1/2" for OS)	5-9 3/4
For 1 SL Combinations:	(+4)	(+3")	(+5-1/2")	
1-0x3-0	4-4	4-3	4-5 ½ (+1/2" for OS)	4-1 ½
For 2 SL Combinations:	(+5-1/2)	(+4-1/2")	(+7")	
1-0x3-0x1-0	5-5 ½	5-4 ½	5-7 (+1/2" for OS)	5-3
Center Hinged Patio Units				
For Patios:	(+3-13/16")	(+2-13/16")	(+5-5/16")	(+1-5/16")
5-0	5-3 13/16	5-2 13/16	5-5 5/16 (+1/2" for OS)	5-1 5/16
5-4	5-7 13/16	5-6 13/16	5-9 5/16 (+1/2" for OS)	5-5 5/16
6-0	6-3 13/16	6-2 13/16	6-5 5/16 (+1/2" for OS)	6-1 5/16
5-0 SFG Retro Patio	5-1 1/4	5-0 1/4	5-2 3/4 (+1/2" for OS)	4-10 3/4
6-0 SFG Retro Patio	6-1 1/4	6-0 1/4	6-2 3/4 (+1/2" for OS)	5-10 3/4
7-6	7-11 1/8	7-10 1/8	8-0 5/8 (+1/2" for OS)	7-8 5/8
8-0	8-5 1/8	8-4 1/8	8-6 5/8 (+1/2" for OS)	8-2 5/8
9-0	9-5 1/8	9-4 1/8	9-6 5/8 (+1/2" for OS)	9-2 5/8
Call Size Heights:	(+3-1/4")	(+2-3/4")	(+4")	
6-8 (6-7 net)	6-10 ¼	6-9 ¼	6-11 (+1/4" for OS)	
7-0 (6-11 net)	7-2 ¼	7-1 ¼	7-3 (+1/4" for OS)	
8-0 (7-11 net)	8-2 ¼	8-1 ¼	8-3 (+1/4" for OS)	
AD & RD	Add 1" but VERIFY WITH DSL			
All Transoms	Add Door RO Height to Transom Size + 1 ½"			
Handicap Sill (HC)	Deduct 1"	Deduct 1"	Deduct ¾"	
Outswing Std.	Deduct 5/8"	Deduct 5/8"	Deduct 3/8"	
Outswing HC	Deduct 1"	Deduct 1"	Deduct 1"	

(864) 242-6571
 (864) 242-0433 fax
www.victorbilt.com
info@victorbilt.com

