




### A TRADITION OF

BUILDING
THE INDUSTRY'S
FINEST COLUMNS
FOR OVER
FORTY YEARS.

Turncraft, a division of Cascade Wood
Products (established in 1949), is built
on a rich tradition of creating quality
products from premium materials. Since
manufacturing our first column in 1963,
architects and builders have chosen Turncraft
columns because of our thoughtful design,
exceptional materials, fine workmanship,
superior assembly, and extensive selection.
Precise historical research and authentic
architectural specifications reflect our
dedication to the quality you can expect from
all of our products—from in-stock columns
to custom-built solutions.

For homeowners, builders and architects who will not settle for anything less than the finest materials and craftsmanship, Turncraft offers the architectural columns, posts and railings of choice. Beautiful. Durable. Versatile. Functional. Available in classic as well as contemporary choices to compliment any style. Choose from natural wood or virtually maintenance-free materials designed to stand beautifully for years.



# Flow to Select YOUR TURNCRAFT COLUMN OR POST

#### (or which Turncraft column or post is right for you)

To determine which product is the best for your project, you'll want to consider several things: location, style, size, and plan type. Not all styles, sizes or plan types are made in all materials.

All Turncraft products (except the Craftsman Series) are manufactured whole and are designed to be load bearing. If you need to wrap an existing load support, all of our columns are able to be split in half at the factory or by the installer and re-assembled, or they can be split to be used as pilasters.

Craftsman Series columns are square, tapered or non-tapered, and are shipped KD (knocked-down) to be assembled around an existing load support. Craftsman Series pedestals are unique in that they may be used to add a pedestal look to any existing column, or combined with any of our other products to create a pedestal/column look.

#### I. DETERMINE THE LOCATION.

Where this product will be used – interior or exterior. All of our products are fine for interior use. Wood may be a more familiar material to work with, but all products can be installed with standard carpentry techniques and tools.

Best for exterior: Poly-Classic® products (low maintenance, lifetime warranty, waterproof), and Turncraft Architectural redwood or cedar columns. A large selection of styles are available. Poly-Classic® products require painting (except DuraStone™ columns and Poly-Classic® Porch Posts).

#### Poly-Classic® column products include:

FRP columns (fiberglass reinforced polymer)

DuraGlass columns (resin-infused or pultruded fiberglass)

Craftsman Series (PVC–expanded cellular poly-vinyl-chloride)

DuraStone<sup>™</sup> columns are a unique product that are available in three colors – sand, ivory and slate – and textured to resemble stone. These columns do not require paint.

Colonial wood columns are also used for exterior installations. Turncraft Architectural exterior columns are usually made of redwood, cedar or pine. Redwood and cedar have a 10 year limited warranty, and pine has a 1 year limited warranty. Exterior wood products require painting. Turncraft Architectural also provides our most complete selection of styles and sizes, including interior stain grade columns.

Colonial wood columns and posts are made of finger joint pine. Columns have a 1 year limited warranty. All porch posts are covered by our lifetime limited warranty and Post Defense program. Colonial wood products require painting.

#### II. DETERMINE THE PLAN TYPE.



#### III. DETERMINE THE STYLE.

Perhaps most important, is of course style. This includes the classical orders of architecture: Greek Doric, Tuscan, Roman Doric, Ionic and Corinthian, with the addition of our own Colonial style. All round columns are available plain or fluted (except DuraGlass), and most square columns are available plain, fluted or with panels.

www.Turncraft.com 5

#### STYLES AND DESIGN CHARACTERISTICS



# Zuscan

Available in:

FRP	Poly-Classic° FRPpages 10–19
DST	DuraStone <sup>™</sup> FRP pages 20–21
DGL	DuraGlass Fiberglass pages 22–25
<b>CRF</b>	Craftsman PVCpages 28–35
ARC	Architectural Wood pages 36–41

#### SIMPLICITY GIVES YOUR DESIGN CENTER STAGE.

The distinguishing characteristic of the Tuscan Order is simplicity. Seldom fluted, the minimal mouldings and stylishly clean lines provide a robust appearance. When used in true architectural proportions, the height of the column, including cap and base, is seven diameters. Tuscan columns in antiquity are found on the Temple of Piety in Rome.



# Roman Dovic

Available in:

FRP Poly-Classic® FRP...... pages 10–19
ARC Architectural Wood...... pages 36–41

#### CLASSIC DESIGN REACHES NEW HEIGHTS.

The Roman Doric order features an increase of decorative moulding over the Tuscan Order. Vignola's Denticulated Doric Cap has a stepped, three-fillet support of the echinus instead of the single-fillet support of the Tuscan Order. The Doric base is similar to the Tuscan, but the addition of a bead above the torus moulding is an elegant embellishment. According to Vignola, the height of the Doric Column, including cap and base, should be eight diameters. Vignola Denticulated Doric is imitated closely from the Roman Theater of Marcellus.



## Tonic

Available in:

FRP	Poly-Classic° FRP pages 10–19
DST	DuraStone <sup>™</sup> FRP pages 20–21
<b>CRF</b>	Craftsman PVC pages 28–35
ARC	Architectural Wood pages 36–41

#### ADDED EMBELLISHMENTS CREATE IMPRESSIVE SPACES.

Embellishing the Ionic Order are ornate scrolls decorating the capital of the column. These scrolls derive their intriguing shape from the Nautilus shell. We include the Temple of Winds and Roman Doric Ornamental capitals, with their intricate designs, in our Ionic styles. Most commonly, Ionic columns incorporate twenty-four flutes separated by fillets that are about one-half the flute width. Customarily, the Ionic Order column height, including capital and base, is nine diameters. A prime example of the Ionic Order as it was used in Rome is the Temple of Fortuna Virilis.



# Corinthian

Available in:

FRP	Poly-Classic® FRP pages 10–19
DST	DuraStone <sup>™</sup> FRP pages 20–21
<b>CRF</b>	Craftsman PVC pages 28–35
ARC	Architectural Wood pages 36–41

#### MAKE IT THE CROWNING JEWEL OF YOUR PROJECT.

Columns of the Corinthian Order are crowned with an inverted bell-shaped capital. The capital is richly adorned with Acanthus leaves. This column is almost always fluted. Like the Ionic, the Corinthian column exhibits twenty-four flutes and an Attic Base. The height of Corinthian columns, including capital and base, is ten diameters. This is a common Roman order that was used on the Temple of Mars Ultor.

www.Turncraft.com 7 |



Greek Dovic

Available in:

ARC Architectural Wood...... pages 36–41

#### BRING HOME THE ELEGANCE OF THE PARTHENON.

The Greek Doric Order is unique among column styles with its absence of a base and astragal. The column height in ratio to its diameter varies greatly when viewed in antiquity: the architectural proportions can range from four to six diameters. Normally fluted, the Greek Doric has twenty flutes, with no fillets, so the flutes come to a peak (arris flutes). The depth of the flute is approximately one-sixth of the flute width. Greek Doric columns are most commonly recognized as those found on the Parthenon in Athens.



Wood Colonial

Available in:



#### ELEGANT NEW WORLD ENHANCEMENTS FOR YOUR HOME.

As with many iconic Old World items, New World designers have taken the basic column concept and adorned it with a unique, more contemporary style. The Colonial style redefines the column with simplicity, yet retains the elegance desired to make bold statements for entryways and interiors. Available smooth or fluted, the entire line of ornamental capitals is also available for personalizing the column to fit any décor.



Arts and Crafts
Available in:

CRF Craftsman PVC.....pages 28–35

#### THE STYLE IS TIMELESS. NOW THE COLUMN IS TOO.

Born out of the understated, practical tradition of the early 1900's Arts and Crafts movement, the square tapered column has become popular in modern adaptations of the Craftsman, Prairie, Bungalow, Country, and Mission style homes of today. Also available non-tapered, this timeless style is manufactured from expanded cellular PVC for quick, easy assembly and virtually maintenance-free performance! Now you can recapture the simple, honest artistry of yesterday's craftsman with today's most advanced materials and construction techniques.



Porch Posts

Available in:

WPP Wood Porch Posts ...... pages 46–47

PCP Poly-Classic® Posts...... pages 26–27

#### AN ALL-AMERICAN DECORATIVE TRADITION CONTINUES.

When a column would simply be too much, but a decorative touch is essential, a Porch Post from Turncraft would be the perfect choice. Often featured on Farmhouse and Country style houses with their spacious porches, and Victorian homes with their intricate details, the Colonial pattern is a traditional favorite. Porch Posts add charm and personality to walkways, landings, decks, and porches. There is nothing like the beauty of a Porch Post to add distinction and character to any home.

www.Turncraft.com 9 |



# POLY-CLASSIC® FRP Columns



- STRONGEST COLUMN AVAILABLE
- LOW MAINTENANCE
- WIDE ARRAY OF OPTIONS
- CAN BE SPLIT FOR REASSEMBLY

- LIMITED LIFETIME WARRANTY
- READY TO PRIME AND PAINT
- EXTERIOR OR INTERIOR USE
- MADE WITH FLAME GUARD™

10 |

#### TRANSFORMING STRUCTURES WITH POLY-CLASSIC® FRP C<u>OLUMNS</u>

Turncraft Poly-Classic® FRP Columns are the product of choice for homeowners and builders who demand beauty, value, and performance. Poly-Classic® FRP Columns are architecturally proportioned from rotocast fiberglass-reinforced polymer—the most advanced construction material in the world—so pound for pound they are stronger than concrete, steel, or aluminum.

#### LIMITED LIFETIME WARRANTY

Poly-Classic\* FRP Columns are virtually maintenance-free. They are impervious to termite and carpenter ant attack as well as staining and decaying fungi. High-humidity environments have no effect on these non-porous, waterproof columns. All Turncraft Poly-Classic\* Columns are covered by a limited lifetime warranty to the original purchaser. Warranty details are available from your distributor or our website—www.Turncraft.com.


#### NOW WITH FLAME GUARD™

Poly-Classic® FRP Columns were the first fiberglass-reinforced polymer columns to achieve the distinction of passing an industry test (ASTME, 84-01) that measures the flame spread and smoke development of building components in a fire.

AWIL	rncraft Poly-Classic® FRF th Flame Guard set a new i									
G	Flame Spread Index (FSI)	Smoke Developed Index (SDI)								
Industry Standard for FRP Columns	70-85	900-1025								
Turncraft Poly-Classic® Columns	335**									
*Achieving Class I Flame-Spread classification under 1997 uniform fire code. **Well below the allowable SDI index of 450.										

#### PLAN TYPES

Poly-Classic\* FRP Columns are available in the plan types below. Please specify when you order. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc.)



Pedestal

Square



www.Turncraft.com 11 |




#### TIMESAVER CAP AND BASE

New to the Turncraft product line, our 8" Square TimeSaver Cap and Base employs the same QuickFit installation pressure tabs as our round 8", 10", and 12" TimeSaver products. Our TimeSaver cap and base offers the easiest and quickest installation in the industry.






- Patent pending pressure tabs
- Made out of fiber-reinforced recycled ABS (acrylonitrile butadiene styrene)
- Designed for use on round FRP columns in 8", 10", and 12" sizes
- Made with 95% recycled material
- Extremely strong and durable
- Self aligning with no fasteners
- Excellent paint adhesion
- Fast installation



#### TIMESAVER RAILING ADAPTER BRACKET


Our TimeSaver railing adapter bracket solves the age old problem of attaching a railing system to the decorative base of a round column. Simply use one of these new brackets to make an attractive attachment to our 8", 10", and 12" round Tuscan bases. Brackets are available in two different heights, allowing them to be used with just about any railing system on the market.



#### **NEW!** COPPER OR ALUMINUM FLASHING

Turncraft is now offering real flashing for our most popular sizes of columns - the 8", 10", and 12" round and square Poly-Classic° FRP columns with Tuscan caps. Flashing is available in either copper or aluminum. Flashing is 3/4" larger than abacus size, to be folded over the edges of the cap,

held in place with construction adhesive (not supplied). Flashing for other sizes and styles of caps are available. Call for more information.



#### INSTALLATION KITS AVAILABLE

#### **INSTALL KIT**

For structural FRP columns, the install kit consists of 4 ABS brackets (2 for top of column and 2 for bottom) and fasteners required for standard installation. We recommend



2 kits for columns 16" and up: this will allow the installer to use 4 brackets at the top and bottom of the column. When installed, the cap and base will conceal these brackets and hardware.

#### SPLIT KIT

Each kit contains six nylon locking straps with 1/8" spacers and one quart (1.85 lb.) automotive body filler. For columns over 12 foot in height, two kits will



be required per column. Turncraft recommends using an abrasive (Carborundum or similar) or carbide blade to trim the shaft. Split columns are not load bearing.



#### **ROUND COLUMN SIZES**

Round tapered and non-tapered shafts are available fluted and unfluted in a wide range of sizes. Flutes in most 8", 10", and 12" diameter tapered shafts are molded right into the shaft, providing consistent Ionic fluting. All sizes can also be custom-fluted for specific opening heights, and adjusted for the cap and base chosen. When shafts are custom fluted, typically the flutes end 1" from the top of the base. Larger 30" diameter columns are available in our DuraGlass product line.

#### **SQUARE COLUMN SIZES**

Square non-tapered shafts are available unfluted, fluted, recessed panel, or with a double raised panel. In addition, custom fluting is available. The astragal is molded into the shaft for consistent spacing and simplified installation.

	Tapered Round FRP Shafts Available Heights and Load Capacities														
Column Bottom Diameter *	5'	6'	8'	9'	10'	12'	14'	16'	18'	20'	22'	24'	Concentric Load ☆	Eccentric Load ☆	
6"	$\checkmark$	$\checkmark$	$\checkmark$										6,000 lb.	6,000 lb.	
8"	$\checkmark$	√	å	å	å								10,000 lb.	6,600 lb.	
10"	$\checkmark$	$\checkmark$	å	å	å	å							14,000 lb.	10,720 lb.	
12"	√	√	å	å	å	å	√	å					18,000 lb.	13,200 lb.	
14"			$\checkmark$			20,000 lb.	11,520 lb.								
16"	√	√	√	√	√	√	√	√	√	√			20,000 lb.	13,200 lb.	
18"			$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	√	$\checkmark$	$\checkmark$	$\checkmark$	20,000 lb.	9,040 lb.	
20"		√	√		√	√	√	√	√	√			20,000 lb.	18,960 lb.	
24"			$\checkmark$		$\checkmark$	20,000 lb.	13,200 lb.								

Non	Non-Tapered Round Shafts Available Heights and Load Capacities													
Column Bottom Diameter*	8'	10'	11'	12'	14'	15'	Concentric Load ★	Eccentric Load ☆						
8"	$\checkmark$	$\checkmark$					10,000 lb.	6,600 lb.						
10"	√	√					14,000 lb.	10,720 lb.						
12"	$\checkmark$	$\checkmark$		$\checkmark$			18,000 lb.	13,200 lb.						
14"	$\checkmark$	√		√	√		20,000 lb.	11,520 lb.						
16"	$\checkmark$	$\checkmark$					20,000 lb.	13,200 lb.						
18"	√	√	√				20,000 lb.	9,040 lb.						
20"	$\checkmark$	$\checkmark$	$\checkmark$				20,000 lb.	18,960 lb.						
24"	$\checkmark$	√		√	√	√	20,000 lb.	13,200 lb.						

Non	Non-Tapered Square Shafts Available Heights and Load Capacities													
Column Bottom Width	8' 9' 10' 12' 14' 16' Concentric Eccentric Load \( \pm \)													
6"	$\checkmark$	√ √ 6,000 lb. 6,000 lb.												
8"	√∙∆◊	√•∆	√∙∆≎				10,000 lb.	6,600 lb.						
10"	√◊	√◊	√◊	$\checkmark$			12,800 lb.	10,720 lb.						
12"	√	√	√	√	√	√	18,000 lb.	17,320 lb.						
14"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	20,000 lb.	17,320 lb.						

- Concentric Eccentric Loading Column Shaft

  Square FRP Column

  Round FRP Column
  - \* Actual shaft width may be smaller than nominal size shown.
  - ★ Load capacities are reduced when loads are not centered.

Full documentation regarding eccentric load capacities can be found online at <a href="https://document.com/pdf/EccentricLoad.pdf"><u>Turncraft.com/pdf/EccentricLoad.pdf</u></a> and <a href="https://document.com/pdf/LoadAddendum.pdf"><u>Turncraft.com/pdf/LoadAddendum.pdf</u></a>.

Please refer to the online documentation regarding maximum eccentricity (beam offset from center) and other specifications.

- $\checkmark$  Available unfluted.
- Available with standard flutes.
- ▲ Available raised panel.
- ♦ Available with recessed panel.

All Poly-Classic® FRP Columns are available with custom fluting.

www.Turncraft.com

#### POLY-CLASSIC\* FRP COLUMN ROUND TAPERED SHAFT SPECIFICATIONS



Column	Shaft		aft om *	Sh top		Space a		Sh ne		Flute	Straight portion	Straight portion	Smooth shaft		<del></del>	н —	
nominal diameter	height (A)	Outside diameter (C)	Inside diameter (D)	Outside diameter (H)	Inside diameter (I)	For round post	For square post	Neck height†	Astragal ring #	width (24 each)	of shaft (unfluted) (B)	of shaft (fluted)	before flutes (E)				
6"	5' 6' 8'	5 11/16"	4 3/4"	4 13/16"	3 ¾"	3 %"	2 ½"	3"	1/2"	1/2"	23 ½6" 35 ½6" 59 ½6"	n/a	n/a				
8"	5' 6' 8' 9'	7 %"	6¾"	6 1%32"	5 ½"	5 ½"	3 ½"	4 ¼"	½"	11/16"	14 ½6" 26 ½6" 50 ½6" 62 ½6" 72 ½6"	n/a n/a 50" 54" 65"	n/a n/a 9¾" 9¾"				
10"	4' 5' 6' 8' 9' 10' 12'	9 11/16"	8 3/8"	8 %6"	7 ¾"	7 %"	4 15/16"	5 1/8"	3/4"	7≰"	0 0 10 11/46" 34 11/46" 46 11/46" 58 11/46" 82 11/46"	n/a n/a n/a 39" 56" 65"	n/a n/a n/a 10 ¼" 10 ½" 10 ½"				
12"	5' 6' 8' 9' 10' 12' 14' 16'	11 %"	10 ¾"	10 1/4"	9 ¼"	8 %"	6"	4 ¾"	3/4"	1"	0 8 ¾" 32 ¾" 44 ¾" 56 ¾" 80 ¾" 62" 86"	n/a n/a 42 ¾" 49" 53" 60" n/a 87"	n/a n/a 11 ¼" 11 ¼" 11 ¼" 11 ¾" n/a 11 ¾"				
14"	8' 9' 10' 12' 14' 16' 18' 20'	13 ½"	11 ½"	11 %"	10 ½"	10 %"	6 3%"	6 ¾"	1"	1 ¼"	33 ¼" 45 ¼" 57 ¼" 81 ¼" 57 ¼" 81 ¼" 105 ¼" 129 ¼"	Top Dial	meter				
16"	5' 6' 8' 9' 10' 12' 14' 16' 18' 20'	15 1/46"	13 ½"	13 %"	12"	11 %"	7 ¾6"	7 %"	1"	1 %°	16 ¼" 28 ¼" 18 ½" 30 ½" 42 ½" 66 ½" 27 ¼" 75 ¼" 99 ¼"	Inside Square	de	A   			
18"	8' 9' 10' 12' 14' 16' 18' 20' 22' 24'	17 %"	15"	14 1/16"	12 ¾"	12 %"	8 1/16"	7 %"	1"	1 ½"	13 ½" 25 ½" 37 ½" 61 ½" 85 ½" 26 ½" 50 ½" 74 ½" 98 ½"	Availal Inside S measur are cald at the t	ble Shaft" rements culated op liameter				
20"	6' 8' 10' 12' 14' 16' 18' 20' 8'	19 %"	18"	16 1/46"	14 %"	14 ½"	10"	9 3/6"	1 %"	1 11/16"	0 22 ¼" 46 ¼" 70 ¼" 40 %" 64 %" 88 %" 112 %"	,	ce), when Iuscan an aps. and	B 			<u></u>
24"	8 10' 12' 14' 16' 18' 20' 22' 24'	23 %"	22"	19 %6"	18"	17 %"	12 ¾6"	12"	1 %"	2 1/3"	8 32" 56" 24 ½6" 48 ½6" 72 ½6" 96 ¼6" 120 ⅙6" 144 ½6"	column have re toleran	ıs will duced				<u> </u>
Refer to p  * Diamet  + Neck He	age 13 ters ma	iy vary	± 1/8".						fthogo	-t1:							)


 $<sup>\</sup>dagger$  Neck Height is the distance from the top of the shaft to the top of the astragal ring,  $\pm$  1/8".  $\ddagger$  Astragal ring is only the ring portion, and does not include the fillet and cove.

#### TUSCAN CAPS AND BASES FOR ROUND TAPERED FRP COLUMNS



All caps, bases, and ornamental capitals are manufactured of low-maintenance materials. Materials for caps and bases will vary based on size and style. Standard Tuscan caps and bases for our 8", 10", and 12" diameter round tapered columns are our new TimeSaver ABS (recycled ABS with fiberglass reinforcement). Since these are molded products, specifications shown are  $\pm 1/8$ ", and subject to change without notice.


		T	uscan Bas	se			Tusca	ın Cap		
Column diameter	Plir	nth	То	rus	Total height	Echinus	Abacus		Total height	Materials available†
	(A)	(B)	(C)	(D)	(B-D)	(E)	(F)	(G)	(E-F)	
6"	8"	1½"	1 ¼"	½"	3 ¼"	1"	11/16"	7½"	2 1/16"	<u>P</u> , D
8"	10 %"	1%"	1¾"	%"	4 1/4"	15/16"	1¾"	9 %"	2 11/16"	$\underline{A}, F, D, P$
10"	13 ½"	2 %"	2 %"	3/4"	5 ¼"	1 13/16"	1¾"	12 %"	3 %6"	$\underline{A}$ , F, D, P
12"	16 ¼"	2¾"	2 ¾"	%"	6"	1%"	2"	14%"	3 %"	$\underline{A}$ , F, D, P
14"	18 %"	3 1/46"	3"	1"	7 1/4"	2½"	2 1/46"	17"	4 15/16"	<u>P</u> , D
16"	21 1/4"	3 %"	3 ¾"	1 %"	8 1/4"	2¾"	2 11/16"	19 ½"	5 1/6"	<u>P</u> , D
18"	24"	4 1/16"	4"	1%"	9 %6"	3"	215/16"	21 %"	5 15/16"	<u>P</u> , D
20"	27"	4¾"	4 1/46"	1¾"	10 %"	3 1/8"	3 1/46"	24 ¼"	6 %6"	<u>P</u> , D
24"	32 ½"	5¾"	5 ¼"	2 1/4"	13 ¼"	3 1/46"	4 1/8"	28 ¾"	7 1/4"	<u>P,</u> D




<sup>†</sup> A-ABS TimeSaver, F-FRP, D-Durastone™, P-Polyurethane cap with FRP base; standard material is <u>underlined</u>

#### ROMAN DORIC CAPS AND BASES FOR ROUND TAPERED FRP COLUMNS

		Ron	nan Doric F	Base †	Roman Doric Cap †				
Column diameter	Pli	nth	То	rus	Total height	Echinus	Aba	acus	Total height
	(A)	(B)	(C)	(D)	B-D)	(E)	(F)	(G)	(E-F)
6"	7 31/32"	1 ½"	1"	3/4"	3 ¼"	1"	1 ¼"	8"	2 ¼"
8"	10 %"	1 %"	1 1/16"	<sup>15</sup> / <sub>16</sub> "	4 1/4"	1 1/16"	1 ½"	10 ¼"	2 15/16"
10"	13 ½"	2 %"	1 ¾"	1 ¼"	5 %"	1 %"	1 ¾"	13"	3 %"
12"	16 %"	2 ¾"	2 1/16"	1 %"	6 1/16"	2 1/8"	2 %"	15 %"	4 ½"
14"	18 ¾"	3 %"	2 %"	1 %"	7 %"	2 11/16"	2 ¾"	17 13/16"	5 %6"
16"	21 ½"	3 %"	2 %"	2"	8¾"	3 ¾6"	3 1/8"	20 1/46"	6 1/16"
18"	24 1/4"	4 1/4"	3 ¼"	2 %"	9 %"	3 1/16"	3 ½"	22 ½"	6 15/16"






#### OPTIONAL ATTIC BASES FOR ROUND FRP COLUMNS

				Attic Base †							
Column diameter	Pli	nth		Torus							
	(A)	(B)	(C)	(D)	(E)	(F)	(B-F)				
6"	8"	1"	3/4"	3/4"	1/2"	1/2"	3 ½"				
8"	10 %"	1 %"	1 %"	<sup>7</sup> ∕8"	3/4"	1/2"	5 %"				
10"	13 ½"	2 %"	1 1/4"	1 %"	₹8"	5/8"	6 1/4"				
12"	16 1/8"	2 ¾"	1 ½"	1 %"	1"	5%"	7 1/4"				
14"	18 ½"	3 1/16"	1 ¾"	1 %"	1 1/4"	11/16"	8 21/32"				
16"	21 3/16"	3 ¾"	2 1/8"	1 %"	1 ½"	13/16"	10 1/8"				
18"	23 15/16"	4 1/4"	2 1/16"	2 1/8"	1 1/16"	1 1/8"	11 1/4"				
20"	27 1/16"	4 3/4"	2 11/16"	2 %"	1 ¾"	1 1/16"	13"				
24"	32 ½"	5 3/4"	3 1/16"	2 13/16"	2 1/8"	1 ¾"	15 ¾"				






#### BUILDERS SERIES CAPS AND BASES FOR ROUND TAPERED FRP COLUMNS

		Build	ers Series I	Base †		Builders Series Cap †				
Column diameter	Pli	nth	То	rus	Total height	Echinus	Aba	acus	Total height	
	(A)	(B)	(C)	(D)	(B-D)	(E)	(F)	(G)	(E-F)	
8"	10 %"	1 %"	1 1/4"	5%"	3 ¾"	1 1/4"	1 1/4"	9 1/16"	2 ½"	
10"	13 ½"	2 %"	1 %"	%6"	4 %6"	1 13/16"	1 ¾"	12 3/16"	3 %6"	
12"	16 1/4"	2 ¾"	2"	7∕8"	5 %"	1 %"	2"	14 %"	3 %"	

<sup>†</sup> Cap and base are polystyrene (with foam core). Not available in DuraStone™.




www.Turncraft.com 15 |

#### POLY-CLASSIC® SHAFTS FOR ROUND NON-TAPERED FRP COLUMNS



Standard FRP column shafts are the same height as the listed size. Tuscan caps and bases and Attic bases go around the shaft, and do not affect the overall height. Ornamental capitals are not typically available for non-tapered round shafts.


0.1	Shaft	Shaft dia	meters *	Space availab	le inside shaft	T1 .		
Column nominal diameter	height	Outside diameter	Inside diameter	For round post	For square post	Flute width (24 each)	Concentric Load	Eccentric Load
diameter	(A)	(B)	(C)	post	post	(2-7 Cacil)		
8"	8' 10'	7 %"	6 ¾"	6 3/8"	4 ½"	11/16"	10,000 lb.	6,600 lb.
	8'							
10"	10'	9 11/16"	8 %"	8"	5 ¾"	7∕8"	14,000 lb.	10,720 lb.
	8'							
12"	10'	11 %"	10 ¾"	10 %"	7 1/16"	1"	18,000 lb.	13,200 lb.
	12'							
	8'							
14"	10'	13 ½"	11 ½"	11 ½"	7 %"	1 5/16"	20,000 lb.	11,520 lb.
17	12'	13 /2	11 /2	11 / 8	, /8	1 /10	20,00010.	11,52010.
	14'							
16"	8' 10'	15 1/46"	13 ½"	13 1/8"	9 1/4"	1 ½"	20,000 lb.	13,200 lb.
	8'							
18"	10'	17 %"	15"	14 %"	10 %"	1 11/16"	20,000 lb.	9,040 lb.
	11'						,_,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
	8'							
20"	10'	19 %"	18"	17 %"	12 ½"	1 %"	20,000 lb.	18,960 lb.
	11'							
	8'							
	10'		21 1/4"					
24"	12'	23 3/8"	(top ID)	20 7/8"	15"	2 5/16"	20,000 lb.	13,200 lb.
	14'		(top ID)					
	15'							



#### TUSCAN CAPS AND BASES FOR ROUND NON-TAPERED FRP COLUMNS


			Tu	scan B	ase				Tuscan	Tuscan Cap						
Column diameter	Pli	nth	To	rus	Total height	Materials available †	Echinus	Aba	acus	Total height	Materials available †					
	(A)	(B)	(C)	(D)	(B-D)		(E)	(F)	(G)	(E-F)	avanabie †					
8"	10 %"	1 %"	1 ¾"	5∕8"	4 1/4"	<u>A,</u> F, D	1 13/16"	1 ¾"	12 1/8"	3 1/16"	<u>P</u> , D					
10"	13 ½"	2 %"	2 1/8"	3/4"	5 1/4"	<u>A,</u> F, D	1 %"	2"	14 %"	3 %"	<u>P</u> , D					
12"	16 ¼"	2 ¾"	2 %"	7∕8"	6"	<u>A,</u> F, D	2 ½"	2 1/16"	17"	4 13/16"	<u>P</u> , D					
14"	18 %"	3 ⅓₁₀"	3"	1"	7 1/16"	<u>F</u> , D	2 ¾"	2 11/16"	19 %"	5 ¾ <sub>16</sub> "	<u>P</u> , D					
16"	21 1/16"	3 %"	3 %"	1 1/8"	8 1/16"	<u>F</u> , D	3"	2 15/16"	21 1/16"	5 15/16"	<u>P</u> , D					
18"	24"	4 ¾6"	4"	1 %"	9 %6"	<u>F</u> , D	3 1/8"	3 1/16"	24 1/4"	6 1/16"	<u>P</u> , D					
20"	27"	4 ¾"	4 1/16"	1 ¾"	10 %6"	<u>F</u> , D	3 ¾6"	4 1/8"	28 ¾"	7 ⅓₁₀"	<u>P</u> , D					
24"	32 ½"	5 ¾"	5 ¼"	2 1/4"	13 ¼"	<u>F</u> , D	3 ¾6"	4 1/8"	32 ½"	7 ⅓₁₀"	<u>P</u> , D					






#### OPTIONAL ATTIC BASES FOR ROUND FRP COLUMNS

				Attic Base	†		
Column diameter	Pli	nth		То	rus		Total height
	(A)	(B)	(C)	(D)	(E)	(F)	(B-F)
6"	8"	1"	3/4"	3/4"	1/2"	1/2"	3 ½"
8"	10 %"	1 %"	1 1/8"	7∕8 <b>"</b>	3/4"	½"	5 1/8"
10"	13 ½"	2 %"	1 1/4"	1 1/8"	7/8"	5/8"	6 ¼"
12"	16 1/8"	2 ¾"	1 ½"	1 %"	1"	5/8"	7 ¼"
14"	18 ½"	3 1/16"	1 3/4"	1 %"	1 ¼"	11/16"	8 %"
16"	21 3/16"	3 ¾"	2 1/8"	1 %"	1 ½"	<sup>13</sup> / <sub>16</sub> "	10 %"
18"	23 15/16"	4 ¼"	2 1/16"	2 1/8"	1 1/46"	1 1/8"	11 ¼"
20"	27 1/16"	4 ¾"	2 11/16"	2 %"	1 ¾"	1 1/16"	13"
24"	32 ½"	5 ¾"	3 5/16"	2 13/16"	2 1/8"	1 ¾"	15 ¾"





800 423 3311

<sup>\*</sup> Diameters may vary ± 1/8".

#### POLY-CLASSIC® SQUARE SHAFTS FOR NON-TAPERED FRP COLUMNS




Standard FRP column shafts are the same height as the listed size. Tuscan caps and bases, and the pedestal base go around the shaft, and do not affect the overall height. Ornamental capitals are set on top of the shaft (after the shaft is trimmed to the correct position), and will affect the overall height: see the Ornamental Capitals for Square Columns specifications for more information.

~ .	Colum	n shaft	Shaf	t neck	Flute	Space			
Column nominal width	Outside width	Inside width *	Neck height†	Astragal ring #	width 20	available inside	Heights available		
Witatii	(B)	(C)	(E)	(D)	each	shaft *			
6"	5 %"	4 3/4"	3 %"	3/4"	1/2"	4 ½"	8'		
8"	7 %"	5 ¾"	4 ½"	3/4"	11/16"	5 ½"	8', 9', 10'		
10"	9 %"	8 ¾"	5 1/16"	3/4"	7∕8"	8 ½"	8', 9', 10', 12'		
12"	11 %"	10 ¾"	4 ½"	3/4"	1"	10 ½"	8', 9', 10', 12', 14', 16'		
14"	13 %"	12 ¾"	7"	1"	1 ¼"	12 ½"	8', 9', 10', 12', 14', 16'		


8" Fluted column	Bottom of shaft before flutes	Flute length	
(stock)	(F)	(G)	C
8'	10 15/16"	77 13/16"	
9'	10 15/16"	89 13/16"	
10'	22 15/16"	89 13/16"	








The "Space Available Inside Shaft" measurements are calculated at the top inside diameter (with  $\pm$  1/4" tolerance). Inside widths may vary. Ornamental capitals will reduce the inside widths.



#### TUSCAN CAPS AND BASES FOR SQUARE NON-TAPERED FRP COLUMNS

0.1			Tuscan B	ase†		Tuscan Cap †					
Column width	Plin	nth	То	rus	Total height	Echinus	Aba	acus	Total height		
width	(A)	(B)	(C)	(D)	(B-D)	(E)	(F) (G)		(E-F)		
6"	8"	1 ½"	1 1/4"	1/2"	3 ¼"	1"	1 1/16"	8 1/16"	2 1/16"		
8"	11 %"	1 %"	1 ¾"	5 <b>%"</b>	4 ¼"	1 1/16"	1 1/16"	11 ¼"	2 ¾"		
10"	13 ½"	2 %"	2 1/8"	3/4"	5 ¼"	1 13/16"	1 ¾"	13 ¼"	3 1/16"		
12"	17"	2 ¾"	2 %"	7∕8 <b>"</b>	6"	1 %"	2"	17 ¼"	3 %"		
14"	18 13/16" 3 3/8"		2 15/16" 1 1/16"		7 %"	2 ½"	2 1/16"	18 11/16"	4 13/16"		



#### OPTIONAL ATTIC BASES FOR SQUARE FRP COLUMNS


0.1		Attic Base †													
Column width	Plin	nth		To	rus		Total height								
width	(A)	(B)	(C)	(D)	(E)	(F)	(B-F)								
6"	8"	1"	3/4"	3/4"	1/2"	1/2"	3 ½"								
8"	10 %"	1 %"	1 1/8"	7∕8 <b>"</b>	3/4"	1/2"	5 1/8"								
10"	13 ½"	2 %"	1 1/4"	1 1/8"	7/8 <b>"</b>	5%"	6 1/4"								
12"	17"	2 ¾"	1 ½"	1 %"	1"	5%"	7 ¼"								
14"	18 ½"	3 5/16"	1 3/4"	1 %"	1 ¼"	11/16"	8 %"								

<sup>†</sup> Attic bases are FRP. Also available in DuraStone™

#### PEDESTAL BASE FOR SQUARE NON-TAPERED FRP COLUMNS

			]	Pedestal Base :	t		
Column width	Bottom width	Total height	Bottom	Center	Platform	Тор	Top width
	(A)	(B)	(C)	(D)	(E)	(F)	(G)
8"	15"	42 %"	8 11/16"	25 %"	2 1/8"	5 11/16"	8 ¼"

<sup>†</sup> Pedestal bases are FRP. Also available in DuraStone™. Use with Tuscan cap (above) or Ornamental Capitals.



www.Turncraft.com 17 |

<sup>\*</sup> For 8" size, stock fluted shaft value is shown. Paneled and plain shafts are typically 1/2" to 1" greater. † Neck Height is the distance from the top of the shaft to the top of the astragal ring (±1/8").

<sup>‡</sup> Astragal ring is only the ring portion, and does not include the fillet and cove.

#### POLY-CLASSIC® STANDARD CAPITALS FOR FRP ROUND TAPERED COLUMNS



Our standard round capitals install on top of the column and are set on the fillet or the neckring. All of these capitals are structural and will meet the columns' stated load capacities when properly installed.



Shaft		Em	pire		E	mpire wit	th Necki	ng	(	Greek An	gular Ion	nic	Greek Erectheum			
nominal bottom diameter	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *
6"	3 1/8"	9"	8 ¾"	-1"	6 %"	9"	8 ¾"	+3 ¼"	3 %"	9 1/4"	9"	-½"	3 ¼"	6 ¾"	8 ½"	-7/8"
8"	3 ¾"	10"	9"	-1"	7 ¾"	10"	9"	+3 ½"	3 ¾"	9 ½"	9"	-1"	3 ¾"	7 3/4"	11 ¾"	-1"
10"	5 ½"	16"	13 ½"	<b>-</b> 3∕8"	10"	13 ½"	12 ¼"	+4 %"	5 %"	14 1/4"	13 ¼"	-½"	5 ½"	12"	17 ½"	-3%"
12"	6 ¼"	18"	17"	+¾"	11"	18"	17"	+6 1/4"	6"	17 ¼"	17"	+½"	6 ¼"	14 ¼"	21"	+3/4"
14"	7 ¼"	20 ¼"	19 ½"	-3/4"	14 ½"	20 ½"	19 ½"	+7 ½"	7 1/4"	20 ¾"	19 ¼"	-3/4"	7"	15"	21"	-1"
16"	8 ¾"	23"	19 ½"	+5%"	17"	23"	19 ½"	+9 %"	8 %"	20 ½"	19 ½"	+1/4"	9"	17 ½"	26"	+%"
18"	10"	32"	26 ¼"	+3/4"	15"	32"	26 ¼"	+6 3/4"	9 ¾"	24 1/4"	19 ¾"	+1/2"	10 ½"	22"	29"	+1 1/4"
20"	11 ¼"	34"	28"	+1 1/8"	17 ¼"	34"	28"	+8 ½"	11"	29 ¾"	28"	+%"	11"	26"	36"	+%"
24"	12 ¾"	35 ½"	35"	-1 %"	19"	35 ½"	35"	+6 3/4"	12 ¾"	35"	34 ½"	-1 1/8"	13"	30 ½"	43"	-7/8"
30"	n/a				n/a			n/a				15"	31"	45 ½"		

Shaft	Greek	Erectheu	m with No	ecking	Mod	lern Comp	osite	Ron	nan Corint	hian	Roman Doric Ornamental				
nominal bottom diameter	Capital Height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Height adjust *	Capital height	Abacus width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *	
6"	5 ¾"	7 3/4"	11 ¾"	+2 1/8"	7"	8"	+3 %"	7"	9 ½"	+3 %"	4"	8 ¾"	n/a	+1/8"	
8"	7 ½"	10 ½"	15"	+3 ¼"	8 ½"	10 ¾"	+4 1/4"	10 ¼"	12 ¾"	+6"	6"	13 %"	n/a	+1 1/4"	
10"	8 ½"	12"	17 ¼"	+3 %"	12 ¼"	16 ½"	+7 1/8"	13 %"	17 ¾"	+8 ¾"	7"	16 ¼"	n/a	+1 1/8"	
12"	9 ½"	14 ½"	21"	+4 ¾"	14 ½"	19"	+9 ¾"	15 ½"	18 ½"	+10 ¾"	7"	16 ¼"	n/a	+1 ½"	
14"	11 ¼"	15"	21"	+4 1/4"	17"	20"	+10"	17"	22"	+10"	9"	21"	n/a	+1"	
16"	13 ½"	17 ½"	26"	+6 %"		n/a		20"	27"	+12 %"	10 ½"	24"	n/a	+2 3/8"	
18"	15"	22 ½"	29"	+6 ¾"	22 ½"	25"	+14 ¼"	23"	32 ½"	+14 3/4"	12 ½"	28"	n/a	+3 1/4"	
20"	17"	26"	36"	+8 ¼"	22 ½"	25"	+13 ¾"	25 ½"	39"	+16 ¾"	12 ½"	28"	24"	+2 %"	
24"	19"	30 ½"	43"	+6 ¾"		n/a		28 ½"	42"	+16 1/4"		n	/a		
30"	24 ¾"	31"	45 ½"			n/a		37 ½"	46 ½"	n/a		n	/a		

Shaft		Romai	1 Ionic			Scan	nozzi		Temple of Winds			
nominal bottom diameter	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Height adjust *	
6"	2 ¼"	6 ½"	8 1/16"	-1 %"	2 %"	7 ¾"	6 ¼"	-1 ½"	7"	8"	+3 %"	
8"	3"	8 ¼"	10 ½"	-1 ¾"	3"	10 ¼"	9"	-1 ¾"	8"	12"	+3 ¾"	
10"	3 %"	11"	13 %"	-2 1/4"	3 %"	14 ½"	12 ½"	-2"	11 %"	15 ¼"	+6"	
12"	4 ½"	12 ½"	16 ½"	-1"	4 %"	16 ¾"	14"	-5/8"	13 ¾"	17"	+9"	
14"	5 ½"	17 ½"	23"	-2 ½"	5 ½"	19"	16 ¾"	-2 ½"	14"	21 ¼"	+7"	
16"	6 1/8"	17 ½"	22"	-2"	6 ¼"	22 ¼"	18 ½"	-1 %"	16"	23"	+8 %"	
18"	6 ½"	20"	24 ¼"	-2 ¾"	7"	23 ½"	23"	-2 1/4"	18 1/8"	26 ¾"	+9 %"	
20"	8 ¾"	25"	31 ¾"	-1 %"	8 ¾"	26"	21 ½"	-1 %"	21 ¼"	28"	+12 ½"	
24"	9"	25 ¼"	33"	-4 %"	10 ¼"	34 ¼"	29 ½"	-3 %"	23 ¼"	34 ¼"	+11"	
30"	12 ½"	32"	40 ½"		12 ¾"	39"	33"		30"	39"	n/a	

For Empire with Necking, Greek Erectheum with Necking, Modern Composite, Roman Corinthian, and Temple of Winds capitals, trim at this point:

For all other capital styles, trim at this point:

Note: All Capitals are Poly/Resin.

Ornamental

<sup>\*</sup> Height Adjust is based on trimming the shaft at the architecturally correct location.

#### POLY-CLASSIC® QUICK-FIT CAPITALS FOR ROUND TAPERED FRP COLUMNS



Our Poly-Classic\* FRP Quick-Fit Capitals are designed for simple installation. These capitals will slide right over the top of the shaft and will sit on the neckring.









Greek Erectheum

Roman Ionic

Roman Corinthian

Scamozzi

Shaft		Greek E			Roman Ionic					
nominal bottom diameter	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *		
6"	3 ¼"	6 %6"	8 %"	+3/8"	2 3/16"	6"	8"	- <sup>11</sup> / <sub>16</sub> "		

<sup>\*</sup> Height Adjust is based on trimming the shaft at the architecturally correct location.

Shaft	F	Roman C	orinthia	ın	Scamozzi					
nominal bottom diameter	Capital height	Abacus width	Scroll width	Height adjust *	Capital height	Abacus width	Scroll width	Height adjust *		
6"	8 11/16"	11"	n/a	+5 11/16"	2 1/16"	8 %"	8 ½"	-7/16 <b>"</b>		
8"	11 1/46"	14 1/16"	n/a	+7 1/16"	3"	11"	10 13/16"	-1 1/8"		
10"	14 1/16"	18 1/8"	n/a	+9 1/16"	4 1/8"	14 ½"	14 %"	-7/8"		
12"	17"	21 ¾"	n/a	+12 ¼"	4 13/16"	17"	16 %"	+1/16"		

#### POLY-CLASSIC® ORNAMENTAL CAPS FOR SQUARE NON-TAPERED FRP COLUMNS

Square Capitals install on top of the column and are set on the fillet or the neckring. All of these capitals are structural and will meet the columns' stated load capacities when properly installed.




Shaft nominal		Em	pire		Em	pire wit	h Neck	ting	Gr	eek Ang	gular Io	nic	G	reek Ei	ectheu	m	Greek Erectheum with Necking			
bottom diameter							Scroll width	Height adjust*												Height adjust*
6"				+4 1/8"																
8"	5 ¼"	13 ½"	12 ¼"	-1/16"	10"	13 ½"	12 ¼"	+5 ½"	5 %"	14 ¼"	13 ¾"	-¾ <sub>16</sub> "	5 ¼"	10 ½"	15"	-½°	7 ½"	10 ½"	15"	+3"
10"	6 ¼"	18"	17"	+3/8"	11"	18"	17"	+5 15/16"	6"	17 ¼"	17"	+1/8"	6 ¼"	14 ½"	21"	+3/8"	9 ½"	14 ½"	21"	+4 1/16"
12"	7 ¼"	20 ¼"	19 ½"	+1 ¾"	14 ¼"	20 ½"	19 ½"	+9 ¾"	7 1/4"	20 ¾"	19 ¼"	+1 ¾"	7"	15"	21"	+2 ½"	11 ¼"	15"	21"	+6 ¾"
14"	8 ¾"	23"	19 ½"	+3/4"	17"	23"	19 ½"	+10"	8 %"	20 ½"	19 ½"	+3/8"	9"	17 1/2"	26"	+1"	13 ½"	17 ½"	26"	+6 1/2"

Shaft nominal	Mode	rn Con	nposite	Roma	ın Cori	nthian	Roman Doric Ornamental			Romai	n Ionic			Scan	nozzi		Temple of Winds			
bottom diameter			Height adjust*										Height adjust*				Height adjust*			
6"	- 0	10 ¾"		- 0	12"	+4 1/8"	Ü		-	V			-1 1/16"	-			-1 1/16"			
8"	11 ½"	16 ½"	+7"	11 ½"	15"	+7"	6"	14 ¼"	+11/16"	3 5%"	10 ½"	13 ½"	-1 11/16"	3 %"	14 ½"	12 ½"	-1 1/16"	10"	13 %"	+5 ½"
10"	14 ½"	19"	+9 1/16"	14 ½"	18 ½"	+9 1/16"		n/a		4 ½"	12 ½"	16 ½"	-1 ¾"	4 %"	16 ¾"	14"	-1"	11 %"	16 %"	+6 1/16"
12"	17"	20"	+12 ½"	17"	22"	+12 ½"	9"	21"	+3 ½"	5 ½"	17 ½"	23"	0	5 ½"	19"	19 ¾"	0	14"	21 ¼"	+9 ½"
14"	22 ½"	25"	+15 ½"	20"	27"	+13"	10 ½"	24"	+2 ½"		n	/a		6 ¼"	22 1/4"	18 ½"	-1 a"	16"	23"	+9"

<sup>\*</sup> Height Adjust is based on trimming the shaft at the architecturally correct location.

www.Turncraft.com



# POLY-CLASSIC® Dura Stone



- **NEVER NEEDS PAINT**
- **COLORED THROUGHOUT**
- **READY TO INSTALL**
- SAME LOAD CAPACITIES AS THE FRP **COLUMNS**
- AVAILABLE IN IVORY, SAND AND SLATE
- LIMITED LIFETIME WARRANTY
- LOW MAINTENANCE
- CUSTOM COLORS AVAILABLE ON LARGE QUANTITY ORDERS



#### POLY-CLASSIC® DURASTONE™ COLUMNS

Get the strength and durability of our popular Poly-Classic® FRP columns in a natural stone finish. DuraStone™ columns are designed to simulate natural stone and just like in nature, the color and texture may vary slightly. DuraStone™ columns are available in all the same sizes as our paint grade FRP columns with Tuscan caps and bases. (Roman Doric caps are not available). We also have a limited selection of decorative capitals to match the columns. The bases on the larger columns (18" and over) will come in two pieces; when installed the assembly seam will be visible. For specifications and other information please refer to the Poly-Classic® FRP column specifications on pages 13-19.

#### READY TO INSTALL

Poly-Classic® DuraStone™ Columns do not need to be primed or painted. Simply cut to length and install. Poly-Classic® DuraStone™ Columns have the same load-bearing capacity as our standard Poly-Classic® FRP Columns.

#### MAINTENANCE-FREE

Poly-Classic® DuraStone™ Columns are colored throughout utilizing UV inhibitors that will minimize color fade over time. (Turncraft warrants that during the first ten years following the date of installation, the degree of color change will not exceed 17 delta.) Because there is no need for primer or paint, there is also no need for touch-ups. The non-porous design makes the columns impervious to moisture damage.

#### DURASTONE" QUICK-FIT CAPITALS FOR ROUND TAPERED COLUMNS



Greek Erectheum



Roman Ionic



Roman Corinthian



Scamozzi

Shaft	(	Greek E	rectheu	m		Roma	n Ionic	
nominal bottom diameter				Height adjust *				
6"	3 1/4"	6 %6"	8 %"	+3/8"	2 3/16"	6"	8"	-11/16"

\* Height Adjust is based on trimming the shaft at the architecturally correct location.

Shaft	F	Roman C	Corinthi	an		Scar	nozzi	
nominal bottom diameter		Abacus width		Height adjust *				Height adjust *
6"	8 11/16"	11"	n/a	+5 11/16"	2 1/16"	8 5/8"	8 ½"	-¾ <sub>16</sub> "
8"	11 1/46"	14 1/46"	n/a	+7 1/16"	3"	11"	10 13/16"	-1 %"
10"	14 3/16"	18 %"	n/a	+9 1/16"	4 1/8"	14 ½"	14 %"	-7/8"
12"	17"	21 ¾"	n/a	+12 1/4"	4 13/16"	17"	16 %"	+½"

www.Turncraft.com 21 |



# POLY-CLASSIC® Dura Glass Columns DGL

- EASY TO CUT AND INSTALL
- DECAY RESISTANT
- LOW MAINTENANCE
- LIGHTWEIGHT COLUMNS

- NOW AVAILABLE IN 30" ROUND
- IMPACT RESISTANT
- LIMITED LIFETIME WARRANTY
- READY TO PRIME AND PAINT


#### LIGHTWEIGHT FIBERGLASS COLUMNS EASILY HANDLE THE LOAD



Sometimes the most beautiful solutions are the most simple. Poly-Classic® DuraGlass square columns from Turncraft offer the classic beauty that homeowners and commercial property owners appreciate. Made from lightweight fiberglass, these columns are easy to cut, easy to install, and strong enough to carry heavy loads. Like other Poly-Classic® columns, DuraGlass columns are decay resistant and require little maintenance.

#### PLAN TYPES

Poly-Classic® Duraglass Columns are available in the following plan types. Please specify when you order. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc.)





Poly-Classic® DuraGlass Tuscan Non-tapered Square

Poly-Classic<sup>®</sup> DuraGlass Tuscan Non-tapered Square with Neck Molding



Poly-Classic® DuraGlass Tuscan Tapered Round

Poly-Classic® DuraGlass Tuscan Non-tapered Round

www.Turncraft.com 23 |




Column	Shaft	Shaft b	ottom†	Shaf	t top	Space a inside	vailable shaft	T 1
nominal width †	height	Outside width	Inside width	Shaft neck ‡	Astragal ring	For round	For square	Load capacity
	(A))	(B)	(C)	(E)	(D)	support	support	
8"	6' 8' 9' 10' 12'	7 ⅓"	7 ½"	4 ½"	3/4"	6 3/4"	6 ¾"	5,000lb.
10"	6' 8' 9' 10' 12'	9 5%"	9 ½"	5"	3/4"	8 ¾"	8 ¾"	6,000lb.
12"	6' 8' 9' 10' 12'	11 %"	11 %"	5 ½"	3/4"	10 ¾"	10 ¾"	7,0001Ь.
16"	8' 10' 12' 14' 16' 18' 20'	15 %"	15 ¼"	7 %"	1"	14 ¾"	14 ¾"	20,0001Ь.

A |

#### **DURAGLASS SQUARE CAP AND BASE SPECIFICATIONS**

		7	Tuscan Bas	e			Tusca			
Column width	Pli	nth	То	rus	Total height	Echinus	Aba	icus	Total height	Material
	(A)	(B) (C)		(D)	(B-D)	(E)	(F)	(G)	(E-F)	
8"	10 %6"	1 3/4"	1 %"	1/2"	3 %"	1 1/16"	1 %"	10 11/16"	2 11/16"	ABS
10"	12 1%6"	1 ¾"	1 %"	1/2"	3 %"	1 1/16"	1 %"	12 11/16"	2 11/16"	Pultruded FG
12"	17"	2 ¾"	2 %"	7/8 <b>"</b>	6"	1 %"	2"	17 ¼"	3 %"	Polyurethane
16"	22 ¼"	3 %"	3 %"	1 %"	8 %"	2 13/16"	2 ¾"	22 ½"	5 %6"	Fiberglass




## TIMESAVER CAP AND BASE MADE EXCLUSIVELY FOR OUR 8" DURAGLASS SQUARE COLUMN

New to the Turncraft product line is our 8" square TimeSaver cap and base product. This new cap and base employs the same quickfit installation as our round 8", 10", and 12" TimeSaver. Our TimeSaver cap and base offers the easiest and quickest installation in the industry.

#### Customers claim:

"The TimeSaver cap and base has cut our installation time in half."



 $<sup>{\</sup>it + Actual shaft net widths may vary from nominal size shown.}$ 


<sup>‡</sup> Necking is shipped loose for pultruded columns. Spacing shown is typical, but may be adjusted by the installer. (Necking on 16" columns is integrated with the shaft.)

#### **DURAGLASS ROUND TAPERED SHAFTS**



Standard DuraGlass column shafts are the same height as the listed size. Tuscan cap and base and Attic base go around the shaft, and do not affect the overall height. Ornamental capitals are set on top of the column astragal, and will affect the overall height: see the Poly-Classic® Ornamental Capitals specifications (page 18) for available capital sizes and more information.

Column	Shaft	Shaft bo	ottom *	Shaft	top *	Space a inside	vailable shaft	Shaf	t neck	Straight
nominal diameter *	height	Outside diameter	Inside diameter	Outside diameter	Inside diameter	For round	For square	Neck height	Astragal ring	portion of shaft
	(A)	(C)	(D)	(G)	(H)	support	support	(F)	(E)	(B)
	8'									0
	10'									0
	12'									0
	14'									0
	16'									0
30"	18'	30"	29"	24 ½"	23 ½"	23"	16 ¼"	13 %"	2 3/8"	1'-6"
30	20'	30	29	Z4 72	23 72	23	10 74	13 78	2 78	3'-6"
	22'									5'-6"
	24'									7'-6"
	26'									9'-6"
	28'									11'-6"
	30'									13'-6"



\* Actual shaft net diameters may be smaller than nominal size shown



		Tus	scan Ba	ase			7	ľuscan (	Сар	
Column diameter	Pli	nth	Torus		Total height	Echinus	Abacus		Total height	Material
	(A)	(B)	(C)	(D)	(B-D)	(E)	(F)	(G)	(E-F)	
30"	40 ½"	7 ¼"	6 ½"	2 ¾"	16 ½"	4 1/16"	5 %"	35 ¾"	9 1/16"	Fiberglass

Column diameter			Op	tional .	Attic Ba	ıse		
	Plin	ıth		T	orus		Total height	Material
	(A)	(B)	(C)	(D)	(E)	(F)	(B-F)	
30"	40 ½"	7 ¼"	3 %"	3 %"	2 %"	1 %"	19 ¼"	Fiberglass




#### **DURAGLASS ROUND NON-TAPERED SHAFTS**


Standard DuraGlass column shafts are the same height as the listed size. Tuscan caps and bases and Attic bases go around the shaft, and do not affect the overall height. Tuscan bases are used (upside-down) as caps. Ornamental capitals are not available for non-tapered shafts.

Column	Shaft	Shaft b	ottom *	Shaft	top *	Space a inside	vailable shaft
nominal diameter *	height	Outside diameter	Inside diameter	Outside diameter	Inside diameter	For round	For square
	(A)	(B)	(C)	(B)	(C)	support	support
	8'						
	10'						
30"	12'	30"	29"	30"	29"	28 ½"	20 %"
	14'						
	15'						

 $<sup>*</sup>Actual\ shaft\ net\ diameters\ may\ be\ smaller\ than\ nominal\ size\ shown.$ 



6.1		,	Tuscan	Base				,	Tuscan	Сар	
Column diameter	Plinth		Torus		Total height	Echi	nus	Ab	acus	Total height	Material
diameter	(A)	(B)	(C)	(D)	(B-D)	(D)	(C)	(B)	(A)	(B-D)	Material
30"	40 ½"	7 ¼"	6 ½"	2 ¾"	16 ½"	2 ¾"	6 ½"	7 ¼"	40 ½"	16 ½"	Fiberglass



В



#### POLY-CLASSIC®

# Porch Posts



- READY TO INSTALL
- LOW MAINTENANCE
- PROTECTIVE UV INHIBITOR
- RAIL ATTACHMENT INSERT

- SQUARE STEEL CORE
- SEAMLESS WINDOW GRADE VINYL
- READY TO PRIME AND PAINT
- LIMITED LIFETIME WARRANTY





#### THE BEST PORCH POST AVAILABLE

Excellent design, performance and low maintenance are built into every Turncraft Poly-Classic® Porch Post. For easy rail attachment and substantial load-bearing strength, each Poly-Classic® Porch Post has a galvanized steel square core and sturdy inserts at critical connection points. Constructed from seamless window grade vinyl with UV inhibitor, Poly-Classic® Porch Post are delivered with matte white finish, but can be painted to match your project. They will deliver eye-catching beauty for many years to come without the maintenance of traditional products. Installation hardware is included with the post.

#### TURNCRAFT HAS GOT YOU COVERED

Poly-Classic® Porch Posts are covered by our legendary limited lifetime warranty to the original purchaser. Warranty details are available from your distributor or at www.Turncraft.com.

Nominal width	Actual width	height	Base height	weight	Load bearing capacity
5"	4 1/4"	96"	42 1/8"	23	3,000 lb.
5"	4 1/4"	108"	42 1/8"	27	3,000 lb.

Includes two standard brackets.

Larger brackets for uplift (1500 lb.) sold separately.



www.Turncraft.com 27 |



## POLY-CLASSIC®

# Craftsman Series




- MADE FROM EXPANDED CELLULAR PVC
- E-Z LOCK JOINT DESIGN
- ASSEMBLES AROUND A STRUCTURAL SUPPORT
- MIX-N-MATCH

- LOW MAINTENANCE
- LIMITED LIFETIME WARRANTY
- READY TO PRIME AND PAINT
- CUSTOM SIZES AVAILABLE

#### PRECISION MITER JOINTS

Vertical edges of Craftsman shafts (tapered, non-tapered, pedestal and newel post styles) all




incorporate the E-Z Lock miter joint for consistently straight miters.

- 1. Glue both edges.
- 2. Slide first joint (A) together.
- 3. Slide second joint (B) together.
- 4. Nail, screw or clamp to hold assembly until glue is fully cured.

#### PLAN TYPES

Craftsman Series are available in the following plan types. Please specify when you order. (Customer may specify actual returns, wall thicknesses, etc.) Plan O & N are available only as non-tapered.



#### PANEL STYLES AVAILABLE



Plain



Recessed Panel



Prairie Pedestal Raised Panel



Prairie Pedestal Standard Pedestal Recessed Panel







"Square Corner" **Raised Panel** 



Poly-Classic® Craftsman Unfluted Tapered Square





Poly-Classic® Craftsman Non-tapered Square with **Recessed Panels** 

Poly-Classic® Craftsman Raised Panels Non-tapered Square

Poly-Classic® <u>Craftsman</u> Unfluted Non-tapered Square

Poly-Classic® Craftsman Fluted Non-tapered Square



www.Turncraft.com

#### POLY-CLASSIC® CRAFTSMAN TAPERED



Craftsman columns are available plain, or with three different paneled options: raised panel, "square corner" raised panel, and recessed panel. (Since all tooling used for routing the panels is done with round bits, there will always be some radius in the cor-ners. The "square corner" style uses the smallest bit possible to minimize that radius - about 1/8".)

		Shaft dir	nensions			Panel di	nensions †	
Nominal	Bot	tom	To	ор	From	From top	From	Width
width	Outside width	Inside width	Outside width	Inside width	bottom of shaft ‡	of shaft	side of shaft	of routed channel
10"	(B) (C)		(E)	(D)	(F)	(G)	(I)	(H)
10"	9 5%"	8 3%"	5 %"	4 %"	10 ½"	2 ½"	1 1/4"	3/4"
12"	11 %"	10 %"	7 %"	6 %"	10 ½"	2 ½"	1 ½"	1 ¼"
16"	15 %"	14 %"	11 %"	10 %"	10 ½"	2 ½"	1 ½"	1 ¼"
20"	19 %"	18 %"	13 %"	12 %"	10 ½"	2 ½"	1 ½"	1 ¼"
24"	23 %"	22 %"	15 %"	14 %"	10 ½"	2½"	1 ½"	1 ¼"

<sup>†</sup> Dimensions (except width) also apply to recessed panel shafts.

 $<sup>\</sup>pm$  Dimension shown is for standard shafts. On custom height columns the panels start 5  $\frac{1}{4}$ " from the bottom.


Nominal		S	tandard sizes (A)	*	
column width	4'	5'	6'	8'	10'
10"	$\checkmark$	√	√	√	√
12"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
16"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
20"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	√
24"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$

 $<sup>*</sup>Actual \ shaft \ height \ is \ 1/2" \ less \ than \ shown.$ 

Custom sizes may be requested, up to 24' in height, and up to 48" width.


# A C B B

#### POLY-CLASSIC\* CRAFTSMAN TAPERED CAP AND BASE STYLES



6.1		Stan	dard			Cro	wn			Pra	irie	
Column nominal	Ba	se	Ca	ıp	Ba	se	Ca	ιp	Ba	.se	Ca	ър
bottom	Outside	Inside	Outside	Inside	Outside	Inside	Outside	Inside	Outside	Inside	Outside	Inside
width	width	width*	width	width*	width	width*	width	width*	width	width*	width	width*
Witten	(A	<b>(</b> )	(B	3)	(A	.)	(F	3)	(A	()	(F	3)
10"	13 %"	5 %"	9 %"	3 %"	15 %"	5 %"	11 %"	3 %"	13 %"	5 %"	9 %"	3 %"
12"	15 %"	7 %"	11 %"	3 %"	17 %"	7 %"	13 %"	3 %"	15 %"	7 %"	11 %"	3 %"
16"	19 %"	11 %"	15 %"	3 %"	21 %"	11 %"	17 %"	3 %"	19 %"	11 %"	15 %"	3 %"
20"	23 %"	13 %"	17 %"	3 %"	25 %"	13 %"	19 %"	3 %"	23 %"	13 %"	17 %"	3 %"
24"	27 %"	15 %"	19 %"	3 %"	29 %"	15 %"	21 %"	3 %"	27 %"	15 %"	19 %"	3 %"

Plan view of "V" cut - shows jointer biscuit recessed into edge:



The cap and base sets for tapered Craftsman Series columns consist of a platform and a molding. The platforms are factory cut in a "V" shape to allow easy installation around an existing load support. This "V" is reassembled using jointer biscuits (included), PVC cement or polyurethane glue, and nails or screws. (As with all exterior products, non-corrosive fasteners must be used, such as double hot-dipped galvanized screws or nails.) This same "V" cut construction is used for the top platform of Craftsman pedestals. Pedestals being used as newels may be ordered without the platform being "V" cut.

Edge view of "V" cut - shows where the jointer biscuits install:

 $<sup>{\</sup>it *Please specify if you require a larger inside width-option only available on 12" and larger caps.}$ 

#### POLY-CLASSIC® CRAFTSMAN NON-TAPERED




	Shaft dir	nensions	Panel a		Pan	els†	Flu	ites
Nominal width	Net bottom width	Inside bottom width	From bottom of shaft ‡	From top of shaft	From side of shaft	Width of routed channel	Number of flutes	Flute width
	(B)	(C)	(D)	(E)	(G)	(F)		
6"	5 %"	4 %"	16 ¾"	8 ½"	1 ¼"	3/4"	20	1/2"
8"	7 %"	6 %"	16 ¾"	8 ½"	1 ½"	1 ¼"	20	3/4"
10"	9 %"	8 %"	16 ¾"	8 ½"	1 ½"	1 1/4"	20	1"
12"	11 %"	10 %"	16 ¾"	8 ½"	1 ½"	1 1/4"	20	1 1/4"
14"	13 %"	12 %"	16 ¾"	9"	2"	1 1/4"	24	1 1/4"
16"	15 %"	14 %"	16 ¾"	9 ¼"	2 1/4"	1 ¼"	28	1 1/4"
18"	17 %"	16 %"	16 ¾"	9 ½"	2 ½"	1 1/4"	32	1 1/4"
20"	19 %"	18 %"	16 ¾"	9 ¾"	2 ¾"	1 ¼"	36	1 ¼"
22"	21 %"	20 %"	16 ¾"	10"	3"	1 1/4"	40	1 1/4"
24"	23 %"	22 %"	16 ¾"	10 ¼"	3 1/4"	1 1/4"	44	1 1/4"

<sup>†</sup> Dimensions except width also apply to recessed panel shafts.


Nominal		Standa	ard siz	zes (A	)
column width	4'	5'	6'	8'	10'
6"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
8"		√	$\checkmark$		√
10"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$
12"	√	√	√	√	√

Nominal				Standa	ard siz	zes (A	.)		
column width	8'	10'	12'	14'	16'	18'	20'	22'	24'
14"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$					
16"		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$				
18"	$\checkmark$	$\checkmark$	V	$\checkmark$	$\checkmark$	$\checkmark$			
20"		$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$		
22"	$\checkmark$								
24"		$\checkmark$							

Custom widths and heights may be requested in any size up to 24' tall and 48" wide. Cap and base trim and platforms will be adjusted as needed for the revised shaft width.



#### POLY-CLASSIC® CRAFTSMAN NON-TAPERED CAP AND BASE STYLES



						Tuscan	Cap & Bas	e			
Column	Standard cap &	Mission cap &		Ba	ıse				Сар		Prairie cap &
nominal width	base width	base width	Plinth width	Plinth height	Torus height	Base height	Echinus height	Abacus height	Cap height	Abacus width	base width
	(A)	(A)	(A)	(B)	(C)	(B-C)	(D)	(E)	(E-F)	(F)	(A)
6"	6 %"	7 %"	8"	1 ½"	1 3/4"	3 1/4"	1"	1 1/16"	2 1/16"	8 7/16"	8 1/8"
8"	8 %"	9 %"	11 %"	1 %"	2 %"	4 1/4"	1 ¾"	1 %"	2 11/16"	11 ¼"	10 1/8"
10"	10 %"	11%"	13 ½"	2 %"	2 %"	5 ¼"	1 13/16"	1 ¾"	3 1/16"	13 ¼"	12 1/8"
12"	12 %"	13 %"	17"	2 ¾"	3 ¼"	6"	1 %"	2"	3 %"	17 ¼"	14 1/8"
14"	14 %"	15 %"	18 %"	3 %"	4"	7 %"	2 %"	2 %"	5"	19"	16 1/8"
16"	16 %"	17 %"	20 %"	3 %"	4"	7 %"	2 %"	2 %"	5"	21"	18 %"
18"	18 %"	19 %"	22 %"	3 %"	4"	7 %"	2 %"	2 %"	5"	23"	20 1/8"
20"	20 %"	21 %"	24 %"	3 %"	4"	7 %"	2 %"	2 %"	5"	25"	22 1/8"
22"	22 %"	23 %"	26 %"	3 %"	4"	7 %"	2 %"	2 %"	5"	27"	24 1/8"
24"	24 %"	25 %"	28 %"	3 %"	4"	7 %"	2 5%"	2 %"	5"	29"	26 1/8"


www.Turncraft.com 31 |

<sup>‡</sup> Dimension shown is for standard shafts. On custom height columns the panels/flutes start 4" from the top of the base selected, and dimension (G) from the cap (or optional neck moulding).

#### POLY-CLASSIC\* CRAFTSMAN PEDESTALS AND NEWELS









	Shaft v	vidths		nels .rd trim)		nels ie trim)	Pan	iels								
Nominal width	Outside	Inside	From bottom of shaft	From top of shaft	From bottom of shaft	From top of shaft	Width of router channel	From side of shaft			A	vailabl	le heigl	nts		
	(B)	(C)	(D)	(E)	(I)	(E)	(F)	(G)	32"	36"	40"	44"	48"	52"	56"	60"
6"	5 ¾"	4 3%"	4 3/4"	3 ¾"	4 ¾"	2 %"	3/4"	1 ¼"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$			$\checkmark$
8"	7 ¾"	6 ¾"	4 ¾"	3 ¾"	4 ¾"	2 %"	1 ¼"	1 ½"								
10"	9 5%"	8 %"	4 3/4"	3 ¾"	4 3/4"	2 %"	1 ¼"	1 ½"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$			$\checkmark$
12"	11 %"	10 %"	4 ¾"	3 ¾"	4 ¾"	2 %"	1 ¼"	1 ½"							√	√
14"	13 %"	12 %"	5 ¼"	4 1/4"	5 ¼"	3 1/8"	1 ¼"	2"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$			$\checkmark$
16"	15 %"	14 %"	5 ½"	4 ½"	5 ½"	3 %"	1 ¼"	2 ¼"	√	√	√	√	√	√	√	√
18"	17 %"	16 %"	5 ¾"	4 ¾"	5 ¾"	3 %"	1 1/4"	2 ½"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$			
20"	19 %"	18 %"	6"	5"	6"	3 %"	1 ¼"	2 ¾"	√	√	√	√	√	√	√	√
22"	21 %"	20 %"	6 ¼"	5 ¼"	6 1/4"	4 1/8"	1 1/4"	3"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$		$\checkmark$	$\checkmark$
24"	23 %"	22 %"	6 ½"	5 ½"	6 ½"	4 %"	1 ¼"	3 ¼"								
26"	25 %"	24 %"	6 ¾"	5 ¾"	6 ¾"	4 5%"	1 1/4"	3 ½"	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$		$\checkmark$	$\checkmark$
28"	27 %"	26 %"	7"	6"	7"	4 %"	1 ¼"	3 ¾"	√	√	√	√	√	√	√	√
30"	29 %"	28 %"	7 ¼"	6 1/4"	7 ¼"	5 %"	1 ¼"	4"	√	<b>√</b>	<b>√</b>	<b>√</b>	<b>√</b>		<b>√</b>	√

<sup>\*</sup>Typically, pedestals are 4" wider than the column it is supporting, or about the same width as the base of the column which it supports.

#### POLY-CLASSIC® CRAFTSMAN PEDESTAL AND NEWEL CAPS AND BASES







Pyramid Cap

OUU	naara 11tm			Trunce Trun			1 yrumu	Cup
0.1	Standaı	rd Trim		Prairie Trim		Platform	Pyram	id Cap
Column nominal width	Width	Height	Base width	Base height	Top height	Top width †	Cap height ± 1/16"	Cap width
widti	(A)	(B)	(C)	(D)	(E)	(F)	(G)	(H)
6"	6 %"	3 ¼"	8 1/8"	3 1/4"	2 1/8"	7 %"	2 1/16"	7 %"
8"	8 %"	3 ¼"	10 1/8"	3 ¼"	2 1/8"	9 5%"	2 ½"	9 %"
10"	10 %"	3 ¼"	12 1/8"	3 ¼"	2 1/8"	11 %"	2 %"	11 %"
12"	12 %"	3 ¼"	14 %"	3 ¼"	2 1/8"	13 %"	3 ¼"	13 %"
14"	14 %"	3 ¼"	16 1/8"	3 1/4"	2 1/8"	15 %"	3 %"	15 %"
16"	16 %"	3 ¼"	18 1/8"	3 ¼"	2 1/8"	17 %"	4"	17 %"
18"	18 %"	3 ¼"	20 1/8"	3 ¼"	2 1/8"	19 %"	4 %"	19 %"
20"	20 %"	3 ¼"	22 1/8"	3 ¼"	2 1/8"	21 %"	4 13/16"	21 %"
22"	22 %"	3 ¼"	24 %"	3 ¼"	2 1/8"	23 %"	5 3/16"	23 %"
24"	24 %"	3 ¼"	26 %"	3 ¼"	2 1/8"	25 %"	5 %6"	25 %"
26"	26 %"	3 ¼"	28 ½"	3 ¼"	2 1/8"	27 %"	6 5/16"	27 %"
28"	28 %"	3 ¼"	30 1/8"	3 ¼"	2 1/8"	39 %"	6 %"	29 %"
30"	30 %"	3 ¼"	32 1/8"	3 ¼"	2 1/8"	41 %"	6 ¾"	31 %"



Designed with crisp, true architectural detail, Ornamental Capitals artfully capture natural themes and images. Capitals for square Non-tapered Poly-Classic\* Craftsman columns are crafted from poly/ resin, and will ship split in half (to reassemble around the load support). Each style is proportionally scaled for the width of the shaft. The Empire with Necking, Greek Erectheum with Necking, Modern Composite, Roman Corinthian, Roman Doric Ornamental, and Temple of Winds capitals will fit more accurately when the optional neck moulding is included. Since the shafts will be manufactured to be correct with the selected capital, there is no need to worry about a height adjustment value with PVC columns. Larger sizes may be available.




Shaft nominal		Empire		Empir	e with n	ecking	Greek	Angular	Ionic	Gree	k Erectl	neum		k Erectl th necki		Mode	rn Com	posite
bottom diameter	Capital height	Abacus width	Scroll width	Capital height	Abacus width	Scroll width	Capital height	Abacus width	Scroll width									
6"	3 ¾"	10"	9"	7 ¾"	10"	9"		n/a		3¾"	7 ¾"	11 ¾"	5 ¾"	7 3/4"	11 ¾"	8 ½	10 ¾	n/a
8"	5 ¼"	13 ½"	22 ¼"	10"	13 ½"	12 ¼"	5 %"	14 ¼"	13 ¾"	5 ¼"	10 ½"	15"	7 ½"	10 ½"	15"	11 ½	16 ½	n/a
10"	6 ¼"	18"	17"	11"	18"	17"	6"	17 ¼"	17"	6 1/4"	14 ½"	21"	9 ½"	14 ½"	21"	14 ½	19	n/a
12"	7 ¼"	20 ¼"	19 ½"	14 ½"	20 ½"	19 ½"	7 ¼"	20 ¾"	19 ¼"	6 ¾"	15"	20 ½"	11 ¼"	15"	21"	17	20	n/a
14"	8 ¾"	23"	19 ½"	17"	23"	19 ½"	8 ¾"	20 ½"	19 ½"	9"	17 ½"	26"	13 ½"	17 ½"	26"		n/a	
16"	10"	32"	26 ¼"		n/a		9 ¾"	24 ¼"	19 ¾"	10"	22 ½"	29"	15"	22 ½"	29"	22 ½	25	n/a
18"	11 ¼"	34"	28"		n/a			n/a		11"	26"	36"	17"	26"	36"		n/a	
20"	12 ¾"	35 ½"	35"	19"	35 ½"	35"	12 ¾"	35"	34 ½"	13"	30 ½"	43"	19"	30 ½"	43"		n/a	

Shaft	Rom	an Corint	thian	Roman I	Doric Orr	amental	R	oman Ion	ic		Scamozzi	i	Ten	nple of W	inds
nominal bottom diameter	Capital height	Abacus width	Scroll width												
6"	8 ½"	12"	n/a	4 ½"	10 ½"	n/a	3"	8 ¼"	10 ½"	2 %"	10"	8"	7 ½"	10 ½"	n/a
8"	12"	15"	n/a	6"	14 ¼"	n/a	3 %"	10 ½"	13 ½"	3 ½"	11"	9 %"	10"	13 %"	n/a
10"	14 ½"	18 ½"	n/a	7"	16 ¼"	n/a	4 ½"	12 ½"	16 ½"	4 %"	16 ¾"	14"	11 %"	16 %"	n/a
12"	17"	22"	n/a	9"	21"	n/a	5 ½"	17 ½"	23"	5 ½"	19"	16 ¾"	16"	19"	n/a
14"	20"	27"	n/a	10 ½"	24"	n/a		n/a		6 1/4"	22 ¼"	18 ½"	16"	23"	n/a
16"	23"	33 ½"	n/a	12 ½"	28"	n/a	6 ½"	20"	24 ¼"	7 ½"	25"	20 ¼"	18 1/8"	26 ¾"	n/a
18"	25 ½"	39"	n/a		n/a		8 ¾"	25"	31 ¾"	8 ¾"	26"	21 ½"	21 ½"	28"	n/a
20"	28 ½"	42"	n/a		n/a		9"	25 ¼"	33"	10 1/4"	34 ¼"	29 ½"	23 ¼"	34 ½"	n/a

www.Turncraft.com 33 |






Columns are installed around an existing load-bearing support (pressure treated post, steel pole, etc).

- 1. Assemble three sides of the pedestal and slide in place around the structure.
- 2. Install final piece of pedestal around structure.
- 3. Install pedestal trim and top plate on pedestal.
- 4. Assemble 3 sides of column and place on pedestal around structure.
- 5. Install final piece of column around structure.
- 6. Install column cap and base around column and secure to beam and to pedestal.

Designed to wrap around a structural support using our EZ-Lock joint design.




#### CRAFTSMAN SERIES MIX-N-MATCH EXAMPLES



34 800 423 3311





No load support is required, since the FRP column is load bearing (unless split).

The column should be installed following our normal installation instructions, with the exception that the base is not attached: the base should temporarily be held above the height of the pedestal.


The Craftsman pedestal is then assembled around the FRP column, and the pedestal trim installed following the typical pedestal installation instructions.

Following the pedestal assembly, the column base is lowered to the top of the pedestal and attached.

Pedestals can also be installed around existing columns to update and freshen the look.

Please specify if your column is round or square, as well as the width, so that we can correctly cut out the top platform of the pedestal to install around your column.

#### CRAFTSMAN SERIES WITH POLY-CLASSIC® FRP MIX-N-MATCH EXAMPLES



www.Turncraft.com 35 |



# turncraft Architectural Series ARC



- ARCHITECTURALLY CORRECT DETAILS
- ALL ORDERS OF CLASSICAL COLUMNS
- CORRECT PROPORTIONS OR CUSTOM **DESIGNS**
- **INTERIOR AND EXTERIOR**

- WIDEST RANGE OF STYLES AND SIZES
- ANY WOOD SPECIES
- FACTORY OPTIONS INCLUDE PRIMING AND ASPHALT COATING
- REDWOOD AND CEDAR COLUMNS HAVE A 10 YEAR LIMITED WARRANTY

# **Comparison of the Orders**

Roman Doric

Turncraft Architectural wood columns are our premier product for precise attention to detail both in design and quality. Unlike FRP columns, where the manufacturing processes dictate some alterations to details, our wood columns are closest to true architectural specifications such as proportion, fluting and entasis (taper or bow).

Architectural columns are best proportioned when following the suggestions of William Ware (The American Vignola), Robert Chitham (The Classic Orders of Architecture), Palladio and others to emulate the ancient architecture of Greece and Rome. The illustration "Comparison of the Orders" shows how the height and diameter ratio affects columns of a similar diameter. Tip: to determine the correct diameter for a column in the height you need, simply divide the height by the diameter factor given below the style chosen. For example, at a two-story height of 198", an Ionic column (9 diameters)

**Entasis Taper** 

should be 22" in diameter (198/9=22), or a Tuscan column (7 diameters) should be 28" in diameter.

In addition to the round columns shown, Turncraft Architectural can provide wood columns in nonarchitectural proportions, in many plan types, including squares, octagons and pilasters, either straight or tapered, as well as coupled columns, and other custom configurations.

Corinthian

Using our computerized lathes, our wood columns typically have the correct column entasis (taper or bow)

- the lower one-third of the shaft is straight, and the upper two-thirds has a diminishing taper. The "Entasis Taper" illustration shows precisely how this is generated. We also have the ability to customize the shaft taper. For example, straight tapers are common, as well as barrel columns where the center of the shaft is larger than both ends.

Ionic

For exterior use, the recommended wood for shafts is redwood or cedar because of their inherent resistance to insects and wood rot, and they carry a ten year limited warranty.



Greek Doric



Pine is also available, with a one year limited warranty. Cap and base for exterior columns are usually polyurethane (up to 16" columns) or fiberglass (18" and larger).



For interior use, Turncraft is able to manufacture columns from a wide variety of woods. Paint grade woods are typically finger-jointed pine or poplar, and stain grade can be practically any species imaginable.



cherry, maple, and walnut. The examples here show the differences in grain and color. However it's best to keep in mind that the finish used affects the








Our most popular stain grade species are red oak, mahogany, final color, so this isn't an exact match.

www.Turncraft.com 37 |






C1 C			Shaft Spo	ecificatio	ns			Cap Speci	fications
Shaft nominal	Bot	tom	T	ор	Flu	tes	Specif	ications	Materials
bottom diameter	Net O.D.	Net I.D.	Net O.D.	Net I.D.	Number	Width	Abacus width (F)	Cap height (E,D,C)	Wood, Fiberglass, Polyurethane
6"	6"	2 1/4"	5"	2"	20	15/16"	7 %"	2 11/16"	W
8"	8"	4 1/4"	6 ½"	3 ½"	20	1 ¼"	9 ¼"	3 1/16"	W
10"	10"	6 ¾"	8 ¼"	5 ¼"	20	1 %6"	11 %"	3 15/16"	W
12"	12"	7 %"	9 ¾"	6 ¾"	20	1 %"	13 ¾"	4 %"	W
14"	14"	10 %"	11 ¼"	8 ¼"	20	2 1/16"	16"	5 ½"	W
16"	16"	11 1/16"	12 ¾"	9 ¾"	20	2 ½"	18 %"	6"	W
18"	18"	12"	14 ½"	11 ½"	20	2 13/16"	20 ½"	6 ¾"	W
20"	20"	14 1/4"	16"	13"	20	3 1/8"	22 %"	7 %"	W
22"	22"	16 ¼"	18"	15"	20	3 1/16"	25 ¼"	8 ¼"	W
24"	24"	18 ¼"	19 ½"	16 ½"	20	3 ¾"	27 ¼"	8 %"	W

## DORIC INTERCOLUMNIATION

Greek Doric Columns are available in fluted or unfluted versions. They may be ordered in Vignola's architectural proportions or in custom combinations of column lengths and widths as well as in non-tapered cylinders. Square architectural columns and pilasters to match detail of round tapered columns are available.

#### **TUSCAN SPECIFICATIONS**



#### TUSCAN INTERCOLUMNIATION


Tuscan Columns are available in fluted or unfluted versions. They may be ordered in Vignola's architectural proportions or in custom combinations of column lengths and widths as well as in non-tapered cylinders. Square architectural columns and pilasters to match detail of round tapered columns are available.

Shaft Specifications								Tuscan Cap and Base Specifications					
Shaft Nominal	Bott	tom	To	pp	Flu	ites		Base		C	ар	Materials	
Bottom Diameter	Net O.D.	Net I.D.	Net O.D.	Net I.D.	Number	Width	Plinth width (A)	Plinth height (B)	Total height (B,C,D)	Abacus width (I)	Total height (H,G)	Wood, Fiberglass, Polyurethane	
4"	4"	0	3 ¼"	0	18	7/16"	5 %"	1"	2 1/16"	5 1/8"	1 1/16"	WP	
6"	6"	3"	4 ¾"	2 ½"	24	½"	8"	1 ½"	3 ¼"	7 ½"	1 ¾"	WP	
8"	8"	5 ¼"	6 ½"	4 %"	24	<sup>11</sup> / <sub>16</sub> "	10 ¾"	1 %"	4 1/4"	9 %"	2 %"	WP	
10"	10"	7 ¼"	8 ½"	6 %"	24	7∕8 <b>"</b>	13 %"	2 %"	5 ¼"	12 1/8"	3"	WP	
12"	12"	9"	10"	7 3/4"	24	1"	16 1/8"	2 3/4"	6"	14 %"	3 %"	WP	
14"	14"	10 1/8"	12"	9"	24	1 ¼"	18 ¾"	3 %"	7 %"	17 %"	4"	WPF	
15"	15"	11 1/16"	12 ¾"	10"	24	1 11/32"	20 1/8"	3 %"	7 %"	18 3/16"	4 1/16"	WP	
16"	16"	12"	13 ½"	10"	24	1 1/16"	21 ½"	3 %"	8 %"	19 ¼"	4 5%"	WPF	
18"	18"	14 1/4"	15"	12"	24	1 ½"	24 1/4"	4 1/4"	9 5%"	21 ½"	5 %"	WF	
20"	20"	16 ¼"	17"	13"	24	1 11/16"	27"	4 ¾"	10 ¾"	24 ¼"	5 %"	WF	
22"	22"	18 ¼"	18 ½"	15"	24	1 15/16"	29 ¾"	5 ¼"	12 1/8"	26 ½"	6 %"	WF	
24"	24"	20 ¼"	20"	17"	24	2 1/8"	32 ½"	5 ¾"	13 ¼"	28 ¾"	6 %"	WF	
26"	26"	22 1/8"	22"	19"	24	2 1/4"	35"	6 ¼"	14 ½"	31 ½"	7 %"	WF	
28"	28"	24 1/8"	23 ½"	21"	24	2 11/16"	38"	6 3/4"	15 ½"	33 %"	8"	WF	
30"	30"	26 ¼"	25"	22"	24	2 %"	40 ½"	7 ¼"	16 ½"	35 ¾"	8 %"	WF	
32"	32"	27"	27"	23"	24	3"	42 ¾"	7 ¾"	17 ¾"	37 %"	9 ¼"	F	
34"	34"	29"	28 ½"	24 ½"	24	3 ¼"	45 ½"	8 ½"	19 %"	41"	9 5%"	F	
36"	36"	31"	30"	26"	24	3 ¼"	48"	9"	20 %"	42 ¾"	10 ½"	F	

#### ROMAN DORIC SPECIFICATIONS









## ROMAN DORIC INTERCOLUMNIATION

Roman Doric Columns are available in fluted or unfluted versions. They may be ordered in Vignola's architectural proportions or in custom combinations of column lengths and widths as well as in non-tapered cylinders. Square architectural columns and pilasters to match detail of round tapered columns are available.

			Shaft Spec	ifications				Romar	n Doric Cap	and Base	Specification	ons
Shaft	Bott	tom	To	р	Flu	ites		Base		C	ар	Materials
nominal bottom diameter	Net O.D.	Net I.D.	Net O.D.	Net I.D.	Number	Width	Plinth width (A)	Plinth height (B)	Total height (B,C,D)	Abacus width (J)	Total height (I,G,H)	Wood, Fiberglass, Polyurethane
4"	4"	0	3 ¼"	0	18	7/16"	5 ¾"	1"	2 1/8"	5 %"	1 ½"	WP
6"	6"	3"	4 ¾"	2 ½"	24	1/2"	8"	1"	3 ¼"	7 ½"	2"	WP
8"	8"	5 ¼"	6 ½"	4 %"	24	11/16"	10 ¾"	1 %"	4 1/4"	9 ¾"	2 %"	WP
10"	10"	7 ¼"	8 ½"	6 ¾"	24	%"	13 %"	2 %"	5 %"	12 ½"	3 1/8"	WP
12"	12"	9"	10"	7 ¾"	24	1"	16 %"	2 ¾"	6 3/16"	14 ¾"	4"	WP
14"	14"	10 1/8"	12"	9"	24	1 ¼"	18 ¾"	3 %"	7 %"	17 ½"	4 11/16"	WPF
15"	15"	11 1/16"	12 ¾"	10"	24	1 11/32"	20 1/8"	3 %"	8 1/16"	18 11/16"	5 1/32"	WP
16"	16"	12"	13 ½"	10"	24	1 1/16"	21 ½"	3 %"	8 ¾"	19 %"	5 %"	WPF
18"	18"	14 1/4"	15"	12"	24	1 ½"	24 1/4"	4 ¼"	9 %"	22 ¼"	6"	WF
20"	20"	16 ¼"	17"	13"	24	1 11/16"	27"	4 ¾"	11"	25"	6 ¾"	WF
22"	22"	18 ¼"	18 ½"	15"	24	1 15/16"	29 ¾"	5 ¼"	12"	27 %"	7 %"	WF
24"	24"	20 ¼"	20"	17"	24	2 1/8"	32 ½"	5 ¾"	13 ¼"	29 ¾"	7 15/16"	WF
26"	26"	22 1/8"	22"	19"	24	2 ¼"	35"	6 ¼"	14 %"	32 ½"	8 11/16"	WF
28"	28"	24 1/8"	23 ½"	21"	24	2 11/16"	38"	6 ¾"	15 %"	34 %"	9 %"	WF
30"	30"	26 ¼"	25"	22"	24	2 %	40 ½"	7 ¼"	16 %"	37"	9 15/16"	WF
32"	32"	27"	27"	23"	24	3"	42 ¾"	7 ¾"	17 ¾"	39 ¼"	10 %6"	F
34"	34"	29"	28 ½"	24 ½"	24	3 ¼"	45 ½"	8 ½"	19 ¼"	42 1/8"	11 1/16"	F
36"	36"	31"	30"	26"	24	3 ¼"	48"	9"	20 ¼"	44 1/8"	12"	F

#### **ROMAN IONIC SPECIFICATIONS**





## IONIC INTERCOLUMNIATION

Ionic Columns are available in fluted or unfluted versions. They may be ordered in Vignola's architectural proportions or in custom combinations of column lengths and widths as well as in nontapered cylinders. Square architectural columns and pilasters to match detail of round tapered columns are available.

39 |

			Shaft Sp	ecificatio	ons		Roman Ionic Cap and Base Specifications								
Shaft	Bot			ор	Flu	tes			Base			Са	ıp		
Nominal Bottom	Net	Net	Net	Net			Attic	Base Spe	ecifications	Materials	Materials Roman Ionic Specifications*		Materials		
Diameter	O.D.	I.D.	O.D.	I.D.	Number	Width	Plinth Width (A)	Plinth Height (B)	Total height (B,C,D,E,F)	Wood, Fiberglass, Polyurethane	Abacus Width (H)	Capital Height (G)	Wood,** Composite, Poly/Resin		
6"	6"	3"	4 3/4"	2 ½"	24	1/2"	8"	1"	3 ½"	WP	6 1/8"	2 1/4"	WCP		
8"	8"	5 ¼"	6 ½"	4 3/8"	24	11/16"	10 ¾"	1 %"	5 1/8"	WP	8 ¼"	3"	WCP		
10"	10"	7 ¼"	8 ½"	6 %"	24	7/8 <b>"</b>	13 %"	2 %"	6 ¼"	WP	11"	3 %"	WCP		
12"	12"	9"	10"	7 ¾"	24	1"	16 %"	2 ¾"	7 ¼"	WP	12 ½"	4 ½"	WCP		
14"	14"	10 1/8"	12"	9"	24	1 ¼"	18 ¾"	3 %"	8 ¾"	WPF	17 ½"	5 ½"	C P		
15"	15"	11 1/16"	12 ¾"	10"	24	1 11/32"	20 1/8"	3 %"	9 1/16"	WP	17 ½"	5 ½"	C P		
16"	16"	12"	13 ½"	10"	24	1 1/16"	21 ½"	3 %"	10 1/8"	WPF	17 ½"	6 1/8"	C P		
18"	18"	14 ¼"	15"	12"	24	1 ½"	24 ¼"	4 ¼"	11 %"	WF	20"	6 ½"	C P		
20"	20"	16 ¼"	17"	13"	24	1 11/16"	27"	4 ¾"	12 %"	WF	20"	6 ½"	C P		
22"	22"	18 ¼"	18 ½"	15"	24	1 15/16"	29 ¾"	5 ¼"	14 ¼"	WF	25"	8 ¾"	C P		
24"	24"	20 ¼"	20"	17"	24	2 1/8"	32 ½"	5 ¾"	15 11/16"	WF	25 ¼"	9"	C		
26"	26"	22 1/8"	22"	19"	24	2 ¼"	35"	6 ¼"	16 %"	WF	26 ½"	9 ½"	С		
28"	28"	24 1/8"	23 ½"	21"	24	2 11/16"	38"	6 3/4"	18 1/8"	WF	32"	12 ½"	C		
30"	30"	26 ¼"	25"	22"	24	2 %"	40 ½"	7 ¼"	19 ¼"	WF	32"	12 ½"	C		


\*Sizes shown for Roman Ionic Cap. See Ornamental Capital table for sizes of all available styles. \*\*Not all capital styles available in wood, not all styles in all sizes.

www.Turncraft.com

#### ROMAN CORINTHIAN SPECIFICATIONS







### CORINTHIAN INTERCOLUMNIATION

Corinthian Columns are available in fluted or unfluted versions. They may be ordered in Vignola's architectural proportions or in custom combinations of column lengths and widths as well as in non-tapered cylinders. Square architectural columns and pilasters to match detail of round tapered columns are available.

		Shaft Specifications						Roman Corinthian Cap and Base Specifications									
Shaft	Bot		To		Flut				Base			Cap	,				
nominal	Dot	tom	10	ър	Flut	es	At	tic Base S	Specifications	Materials	Specifi	cations	Materials				
bottom diameter	Net O.D.	Net I.D.	Net O.D.	Net I.D.	Number	Width	Plinth width (A)	Plinth height (B)	Total Height (B, C, D, E, F)	Wood, Fiberglass, Polyurethane	Abacus width (H)	Total height (G)	Wood, Composite, Poly/Resin				
6"	6"	3"	4 ¾"	2 ½"	24	1/2"	8"	1"	3 ½"	WPF	9 ½"	7"	WCP				
8"	8"	5 ¼"	6 ½"	4 ¾"	24	11/16"	10 ¾"	1 %"	5 1/8"	WPF	12"	8 ½"	WCP				
10"	10"	7 ¼"	8 ½"	6 ¾"	24	7/8 <b>"</b>	13 %"	2 %"	6 1/4"	WPF	15"	12"	WCP				
12"	12"	9"	10"	7 ¾"	24	1"	16 %"	2 ¾"	7 ¼"	WPF	18 ½"	14 ½"	WCP				
14"	14"	10 1/8"	12"	9"	24	1 ¼"	18 ¾"	3 %"	8 ¾"	WPF	22"	17"	C P				
15"	15"	11 1/16"	12 ¾"	10"	24	1 11/32"	20 %"	3 %"	9 1/16"	WPF	22"	17"	CP				
16"	16"	12"	13 ½"	10"	24	1 1/16"	21 ½"	3 %"	10 1/8"	WPF	27"	20"	C P				
18"	18"	14 ¼"	15"	12"	24	1 ½"	24 ¼"	4 1/4"	11 %"	WF	32 ½"	23"	CP				
20"	20"	16 ¼"	17"	13"	24	1 11/16"	27"	4 ¾"	12 %"	WF	39"	25 ½"	C P				
22"	22"	18 ¼"	18 ½"	15"	24	1 15/16"	29 ¾"	5 1/4"	14 ¼"	WF	42"	28 ½"	CP				
24"	24"	20 ¼"	20"	17"	24	2 1/8"	32 ½"	5 3/4"	15 11/16"	WF	42"	28 ½"	C P				
26"	26"	22 1/8"	22"	19"	24	2 1/4"	35"	61/4"	16 %"	WF	42"	32"	С				
28"	28"	24 1/8"	23 ½"	21"	24	2 11/16"	38"	6 ¾"	18 1/8"	WF	46"	34"	C				
30"	30"	26 ¼"	25"	22"	24	2 %"	40 ½"	7 1/4"	19 ¼"	WF	46 ½"	37 ½"	С				


#### **CALCULATED SAFE-LOAD CAPACITIES**

Diameter	Pine	Redwood	Available Heights*
6"	2,567 lb.	5,146 lb.	3' to 10'
8"	4,114 lb.	7,646 lb.	4' to 12'
10"	5,497 lb.	10,474 lb.	5' to 16'
12"	6,620 lb.	12,535 lb.	6' to 20'
14"	11,017 lb.	15,282 lb.	6' to 20'
16"	12,307 lb.	17,343 lb.	6' to 24'
18"	14,487 lb.	19,404 lb.	6' to 24'
20"	16,688 lb.	22,151 lb.	6' to 30'
22"	18,426 lb.	24,212 lb.	8' to 30'
24"	20,018 lb.	26,272 lb.	8' to 30'
26"	22,252 lb.	36,870 lb.	8' to 30'
28"	24,001 lb.	39,519 lb.	8' to 30'
30"	25,746 lb.	42,169 lb.	8' to 30'
32"	42,080 lb.	55,317 lb.	8' to 30'
34"	44,567 lb.	57,476 lb.	8' to 30'
36"	47,054 lb.	61,794 lb.	8' to 30'

The sample columns tested supported loads at least four times the calculated values to the left prior to failure. The load was applied concentrically through the axis of the column. Loads shown are valid only if there is uniform contact between the full area of column ends and the cap and base units. Loads are provided for your convenience only and are not exact values. Consult a structural engineer for the most accurate load estimates.

#### PLAN TYPES

Architectural Columns are available in the following plan types. Please specify when you order. Custom plan types are also available. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc).



<sup>\*</sup> Custom sizes available on request.



#### ORNAMENTAL CAPITALS FOR ARCHITECTURAL WOOD COLUMNS

Shaft nominal	1 Empire		2	2 Empire with Necking			3 Greek Erectheum			4 Scamozzi			5 Greek Erectheum with Necking		
bottom width	Abacus width	Capital height	Scroll width	Abacus width	Capital height	Scroll width	Abacus width	Capital height	Scroll width	Abacus width	Capital height	Scroll width	Abacus width	Capital height	Scroll width
6"	9"	3 %"	8 3/4"	9"	6 %"	8 ¾"	6 ¾"	3 ¼"	8 ½"	7 3/4"	2 %"	6 ¼"		n/a	
8"	10"	3 ¾"	9"	10"	7 ¾"	9"	7 ¾"	4 ½"	11 ¾"	10 ¼"	3"	9"		n/a	
10"	16"	5 ½"	13 ½"	13 ½"	10"	12 ¼"	12"	5 ½"	17 ½"	16"	4 ½"	14"		n/a	
12"	18"	6 3/4"	17"	18"	11"	17"	14 ½"	6 1/4"	21"	17 ½"	5"	15 ½"	14 ½"	9 ½"	21"
14"	20 ½"	7 ¼"	19 ½"	20 ½"	14 ½"	19 ½"	15"	7"	21"	19 ½"	6"	16 ½"	15"	11 ¼"	21"
15"	23"	8 ¾"	19 ½"	20 ½"	14 ½"	19 ½"		n/a		19 ½"	6"	16 ½"	15"	11 ¼"	21"
16"	23"	8 3/4"	19 ½"	23"	17"	19 ½"	17 ½"	9"	26"	22 ¼"	6 1/4"	18 ½"	17 ½"	13 ½"	26"
18"	32"	10"	25 ¼"	32"	15"	26 ¼"	22"	10 ¼"	29"	25"	7 ½"	20 ¼"	22 ½"	15"	29"
20"	34"	11 ¼"	28"	34"	17 ¼"	28"	26"	11"	36"	28 ½"	8 ½"	24"	26"	17"	36"
22"	35 ½"	12 ¾"	35"	34"	17 ¼"	28"	26"	11 ¼"	36 ¼"	28 ½"	8 ½"	24"	26"	17"	36"
24"	35 ½"	12 ¾"	35"	35 ½"	19"	35"	30 ½"	13"	43"	34 ¼"	10 ¼"	29 ½"	30 ½"	19"	43"
26"	37"	13"	35"	37"	19"	35"	32 ½"	13"	43"	35 ¼"	11"	29 ¾"	32 ½"	19 ½"	43"
28"		n/a		37"	19"	35"	31"	15"	45 ½"	39"	12 ¾"	33"	31"	24 ¾"	45 ½"
30"		n/a			n/a		31"	15"	60 ½"	39"	12 ¾"	33"	31"	24 ¾"	45 ½"
36"	n/a n/a				n/a		46" 15" 38 ½"			n/a					

Shaft nominal		oman ithian	7 Roma Ornan		8 Modern Composite		9	Roman Io	nic	10 Gre	eek Angula	r Ionic	11 Temple of Winds	
bottom width	Abacus width	Capital height	Abacus width	Capital height	Abacus width	Capital height	Abacus width	Capital height	Scroll width	Abacus width	Capital height	Scroll width	Abacus width	Capital height
4"	n	/a	n/	'a	n	/a		n/a			n/a		6"	6"
6"	9 ½"	7"	8 ¾"	4"	8"	7"	6 1/8"	2 1/4"	8 1/16"		n/a		8"	7"
8"	12"	8 ½"	13 %"	6"	10 ¾"	8 ½"	8 1/4"	3"	10 ½"	9 ½"	3 ¾"	9"	10 ½"	7 ½"
10"	15"	12"	14 ¼"	6 ¾"	16 ½"	11 ½"	11"	3 %"	13 %"	14 ½"	5 %"	13 ¼"	15 ¼"	11 %"
12"	18 ½"	14 ½"	16 ¼"	7"	19"	14 ½"	12 ½"	4 ½"	16 ½"	17 ¼"	6"	17"	16 %"	11 %"
14"	22"	17"	21"	9"	20"	17"	17 ½"	5 ½"	23"	20 ¾"	7 ¼"	19 ¼"	21 ¼"	14"
15"	22"	17"	24"	10 ½"	20"	17"	17 ½"	6 1/8"	22"	20 ½"	8 %"	19 ½"	21 ¼"	14"
16"	27"	20"	24"	10 ½"	n	/a	17 ½"	6 1/8"	22"	20 ½"	8 %"	19 ½"	23"	16"
18"	32 ½"	23"	28"	12 ½"	25"	22 ½"	20"	6 ½"	24 ¼"	24 ¼"	9 ¾"	19 ¾"	26 ¾"	18 %"
20"	39"	25 ½"	n/	′a	25"	22 ½"	25"	8 ¾"	31 ¾"	29 ¾"	11"	28"	28"	21 ½"
22"	42"	28 ½"	n/	'a	n	/a	25"	8 ¾"	31 ¾"	29 ¾"	11"	28"	34 ½"	23 ¼"
24"	42"	28 ½"	n/	′a	n	/a	25 ¼"	9"	33"	35"	12 ¾"	34 ½"	31 ¼"	28 ½"
26"	42"	32"	n/	'a	n	/a	26 ½"	9 ½"	33 ¾"	39 ½"	14 ¾"	38"	35"	24"
28"	46"	34"	n/	′a	n	/a	32"	12 ½"	40 ½"	39 ½"	14 ¾"	38"	37"	28"
30"	46 ½"	37 ½"	n/	'a	n	/a	32"	12 ½"	40 ½"		n/a		39"	30"
36"	55"	42"	n/	'a	n	/a		n/a			n/a		n	/a



Plaster Ornamental Capitals are coated with boiled linseed oil and turpentine as a temporary protector until they can be primed and coated with at least two coats of oil-base paint on the inside and outside. (If capitals are allowed to gather moisture before painting, peeling is likely to occur and further coating will be futile.) Ornamental Capitals are shipped with a load-bearing plug, which must bear the weight of any load on the column. Specifications and materials are subject to change without notice. Poly/Resin Capitals are load bearing, and do not require plugs.

Exterior and paint-grade interior columns feature polyurethane or fiberglass caps and bases (see charts) to provide crisp, true architectural detail and increased durability. Special-order wood caps and bases are available. Optional aluminum plinths provide an extra measure of protection.

www.Turncraft.com 41 |



#### TIIDNICDAET

# Wood Colonial




- READY TO INSTALL
- WATER-REPELLENT TREATMENT
- AVAILABLE IN 6", 8", 10", AND 12"
- IN STOCK FOR IMMEDIATE SHIPMENT
- READY TO PRIME AND PAINT
- WOOD CAPS AND BASES AVAILABLE FOR INTERIOR USE
- POLYURETHANE CAPS AND BASES AVAILABLE FOR EXTERIOR USE
- TREATED WITH WOODLIFE® 111


## TREATED AND PROTECTED WITH WOODLIFE 111

Non-primed wood Colonial paint grade exterior shafts (except redwood or cedar) are fully immersed in Woodlife® 111 wood preservative. Woodlife® 111 is formulated to protect against staining and decaying fungi, to control shrinking, swelling, end checking, splitting, grain raising, and warping for maximum compatibility with paint, primers, and topcoats. Woodlife® 111 also conforms to Industrial Standard I.S. 4-00, is approved by the N.W.W.D.A., and meets all current and proposed government standards.

#### PLAN TYPES


Colonial columns are available in the following plan types. Please specify when you order. Columns other than Plan Type A are not load bearing. Split or reassembled columns are not load bearing.





Wood Colonial Tapered Round

Wood Colonial Tapered Round Fluted



Wood Colonial Non-tapered Round

Wood Colonial Non-tapered Round Fluted

www.Turncraft.com 43 |

#### ROUND COLONIAL COLUMNS (TAPERED AND NON-TAPERED SHAFTS)



Turncraft manufactures a full selection of Colonial design columns in finger-joint western pine. Other species may be available upon request.

Columns from 14" to 24" diameter are available. Call for more information.


Nominal		Shaft Dim	ensions		Fluting	Dimensions	M. 11	
shaft	Outside	e diameter	Inside d	iameter	Number	Flutes width	Max. load capacity	
diameter †	Bottom	Top‡	Bottom	Top‡	of flutes	riutes width	capacity	
6"	5 %	4 1/4	3	1 ¾	15	1/2	2,095 lb.	
8"	7 %	6 1/4	5	3 ½	15	7∕8	3,258 lb.	
10"	9 %	8 1/4	7 %	5 ½	18	7∕8	4,268 lb.	
12"	11 %	10 1/4	9	7 ½	20	7∕8	5,173 lb.	

<sup>†</sup> Shaft net diameters are 3/8" less than nominal.

<sup>‡</sup> On non-tapered shafts, the top diameters are the same as the bottom.

	Shaft Heights for Non-tapered Columns										
	4' 6' 8' 10' 12'										
6"	$\checkmark$	å	å	$\checkmark \bullet$							
8"	$\checkmark$	å	å	å	$\checkmark$						
10"	$\checkmark$	å	å	$\checkmark \bullet$	$\checkmark \bullet$						
12"	√	$\checkmark$	å	√∙	√∙						

 $<sup>\</sup>checkmark$  Shaft heights for Tapered columns.




#### COLONIAL COLUMN FLUTE SPECIFICATIONS


Actual lengths of the flutes for standard configurations are shown in the accompanying tables. The extra few inches above the base allow the installer to adjust heights as needed to accommodate the variations in porch heights and slopes. Custom flute lengths are available upon request, for the same price as standard fluted columns. Fluting typically ends 4" from the base on custom fluted columns. If using standard height columns with custom height columns, it is best to order the standard height columns custom fluted as well to match the 4" bottom spacing.

	6" Through 12" Diameters									
Column	Tap	pered	Non-tapered							
height	Flute length (A)	Straight shaft (B)	Flute length (A)							
6'	4'-2"	0'	4'-10"							
8'	6'-2"	0'	6'-10"							
10'	8'-2"	2'	8'-10"							
12'	10'-2	4'	10'-10"							

Column	Таре	red *	Non-ta	pered *
diameter	Inside round	Inside square	Inside round	Inside square
6"	1 ½"	1 1/46"	2 %"	1 %"
8"	3"	2 ¼"	4 %"	3 %"
10"	5"	3 %"	6 5%"	4 3/4"
12"	7"	5"	8 5%"	6"



\* For wood columns, inside sizes are based on the inside diameter of the polyurethane cap. Other caps (wood and ornamental capitals) have different sizes and these numbers will not apply.



<sup>•</sup> Shaft heights for Non-tapered columns.

#### COLONIAL COLUMN POLYURETHANE CAP AND BASE SPECIFICATIONS







Tapered and Non-tapered Polyurethane base

Tapered Polyurethane cap

Non-tapered Polyurethane cap

Column	Tapered & Non-tapered Polyurethane Base					Tapered Polyurethane Cap					Non-tapered Polyurethane Cap				
nominal	Plin	nth	Base round		Base	Cap round		Abacus		Cap	Cap Round		Abacus		Cap
diameter*	A	В	C	D	height	E	F	G	Н	height	I	J	K	L	height
6"	8 1/8"	1 1/16"	6 1/8"	1 1/46"	2 %"	5 %"	1 3/16"	6 ¾"	1 ¼"	2 1/16"	6 1/8"	1 1/46"	8 1/8"	1 1/46"	2 %"
8"	10"	1 1/16"	8"	1 1/46"	2 %"	6 ¾"	1 1/46"	8 ¾"	1 ¼"	2 1/16"	8"	1 1/46"	10"	1 1/46"	2 %"
10"	12"	1 1/16"	10"	1 1/16"	2 %"	8 %"	1 1/16"	10 ½"	1 1/46"	2 %"	10"	1 1/46"	12"	1 1/16"	2 %"
12"	14"	1 1/16"	12"	1 1/16"	2 %"	10 %"	1 1/16"	12"	1 1/16"	2 %"	12"	1 1/16"	14"	1 1/16"	2 %"

#### COLONIAL COLUMN WOOD CAP AND BASE SPECIFICATIONS







Tapered and Non-tapered Wood base

Tapered Wood cap

Non-tapered Wood cap

Column	Tapered & Non-tapered Wood Base				Tapered Wood Cap					Non-tapered Wood Cap					
nominal	Pli	nth	Base	round	Base	Cap 1	round	Aba	acus	Cap	Cap F	Round	Ab	acus	Cap
diameter*	A	В	C	D	height	E	F	G	Н	height	I	J	K	L	height
6"	8 1/8"	1 ½"	6 1/8"	1 ½"	3"	5 %"	1 ¼"	6 ¾"	1 ¼"	2 ½"	6 1/8"	1 ½"	8 1/8"	1 ½"	3"
8"	10"	1 ½"	8"	1 ½"	3"	6 ¾"	1 ¼"	8 ¾"	1 ¼"	2 ½"	8"	1 ½"	10"	1 ½"	3"
10"	12"	1 ½"	10"	1 ½"	3"	8 %"	1 ½"	10 %"	1 ½"	3"	10"	1 ½"	12"	1 ½"	3"
12"	14"	1 ½"	12"	1 ½"	3"	10 %"	1 ½"	12"	1 ½"	3"	12"	1 ½"	14"	1 ½"	3"

#### ORNAMENTAL CAPS FOR ROUND TAPERED WOOD COLONIAL COLUMNS







Empire with Necking



Greek Angular Ionic



Greek Erectheum



Greek Erectheum with Necking



Modern Composite



Roman Corinthian



Roman Doric Ornamental



Roman Ionic



Scamozzi



Temple of Winds

Shaft	Empire				E	mpire wit	th Necki	ng	Greek Angular Ionic			
nominal bottom diameter	Capital height	Abacus width				Abacus width				Abacus width		Height adjust
6"	2 ½"	7 ½"	6 ¾"	-4 %"	5"	7 ½"	6 ¾"	-1 1/4"	2 ¾"	7 ½"	6 ¾"	-4 1/8"
8"	3 ¾"	10"	9"	-3 1/8"	7 ¾"	10"	9"	+1 ½"	3 %"	9 ¼"	9"	-3 ¼"
10"	5 ¼"	13 ½"	12 ¼"	-2"	10"	13 ½"	12 ¼"	+3 %"	5 ½"	14 ¼"	13 ¾"	-2 1/8"
12"	6 1/4"	18"	17"	-1"	11"	18"	17"	+4 3/8"	6"	17 ¼"	17"	-1 1/4"

Shaft		Greek E	rectheum		Greek	Erectheu	m with N	Modern Composite			
nominal bottom diameter	Capital height	Abacus width	Scroll width	Height adjust	Capital height	Abacus width	Scroll width	Height adjust	Capital height	Abacus width	Height adjust
6"	3 ¼"	6 ¾"	8 ½"	-3 %"		n	/a		6 ½"	7 ½"	+1/4"
8"	3 ¾"	7 ¾"	11¾"	-3 1/8"	5 ¾"	7 ¾"	11 ¾"	-½"	8 ½"	10 ¾"	+2 1/4"
10"	5 1/4"	10 ½"	15"	-2"	7 ½"	10 ½"	15"	+7/8"	11 ½"	16 ½"	+4 1/8"
12"	6 1//"	14 1/4"	21"	-1"	Q 1/2"	12"	17 1/,"	±1 7⁄6"	12 1/2"	16 1/4"	± <b>5</b> 5%"

For Empire wit Greek Erecther Modern Comp Roman Corinth Temple of Wind trim at this poi	um with Necking, osite, nian, and ds capitals,	
	or all other capital styles, rim at this point:	
· ·	at this point.	

Shaft nominal	Roman Corinthian		Roman Doric Ornamental		Roman Ionic			Scamozzi				Temple of Winds					
bottom diameter	Capital height	Abacus width	Height adjust	Capital height		Height adjust	Capital height	Abacus width	Scroll width	Height adjust	Capital height	Abacus width	Scroll width	Height adjust	Capital height	Abacus width	Height adjust
6"	5 ¾"	8"	-1/2"	4"	8 ¾"	-2 1/4"	2 1/4"	6 1/8"	8 1/16"	-4 <sup>5</sup> %"	2 ½"	6 ½"	5 ¼"	-4 ¾"	6"	6"	-1/4"
8"	8 ½"	12"	+2 1/4"	4 ½"	10 ½"	-1¾"	3"	8 ¼"	10 ½"	-3 %"	2 %"	10"	8"	-4"	7"	8"	+3/4"
10"	11"	13"	+4 %"	6"	14 ¼"	-5%"	3 %"	10 ½"	13 ½"	-3 %"	3 ½"	11"	9 %"	-3 ¾"	10"	13 %"	+3 %"
12"	13 %"	17 ¾"	+7 1/4"	7"	16 ¼"	+3%"	4 ½"	12 ½"	16 ½"	-2 ¾"	4 %"	16 ¾"	14"	-2 <sup>3</sup> / <sub>8</sub> "	11 %"	16 %"	+5"

www.Turncraft.com 45 |



# TURNCRAFT Wood Porch Posts



- REAL WOOD TURNINGS
- SANDED AND PRIMED FOR EASY FINISHING
- SPECIAL SEALER APPLIED TO BOTTOM OF POSTS
- QUICK-MOUNT FASTENERS

- POST DEFENSE LIMITED LIFETIME WARRANTY
- READY TO PAINT
- 4", 5" AND 6" SIZES
- 8', 9' AND 10' LENGTHS





14"

40"

42"

Colonial

Height 8'

#### **CHART KEY**

A: Item Number

B: Width

24"

40"

56"

40"

42"(8') 44"(9') 56"(10')

Square

24"

40"

44"

C: Overall Height

8' 9' 10'

D: Base Height



Cha	Chamfered Post										
A	В	С	D								
D8258AC	5"	8'	42"								
D8259AC	5"	9'	44"								
D8375AC	5"	10'	56"								
D8268AC	6"	8'	42"								
D8269AC	6"	9'	44"								
D8380AC	6"	10'	56"								

Square Porch Post											
A	В	С	D								
D8248A	4"	8'	n/a								
D8249A	4"	9'	n/a								
D8370A	4"	10'	n/a								
D8258A	5"	8'	n/a								
D8259A	5"	9'	n/a								
D8375A	5"	10'	n/a								
D8268A	6"	8'	n/a								
D8269A	6"	9'	n/a								
D8380A	6"	10'	n/a								

Load-Bearing Capacities							
Size 1b.							
4"	1,000						
5"	3,000						
6"	5,800						

	D8268A	6"	8'	n/
	D8269A	6"	9'	n/
	D8380A	6"	10'	n/
	Load	-Bearing	g Capaci	ties
	Size	e	11	).
	4"		1,0	000
	5"		3,0	000
	6"		5,8	300
Porch	ble	tallati	on req	

* Actual	width is	: 13/16 <i>less</i>	than	nominal	widths.

Colonial

Height 9'

Colonial

Height 10'

www.Turncraft.com 47 |

Chamfered

<sup>\*</sup> Post can not be trimmed from the bottom and must be installed on a Quick -Mount  $^{\text{\tiny TM}}$ or other elevated platform for limited lifetime warranty.

# Disit Zurncrafts Website



#### COLUMN BUILDER PDF CREATOR

Our interactive column builder will allow you to choose the column, capital and base of your choice. When you have designed the column you can save it to a PDF for printing. Take the PDF to your local Turncraft distributor for pricing and availability.



#### PHOTO GALLERY

• View Turncraft products installed in various locations.

#### LITERATURE BROWSER

Quick access to all the literature offered on Turncraft website.

#### ARCHITECT'S CORNER

• Specifications and instructions for the architect.

#### **PRODUCTS**

You can select any of our product lines by clicking on the desired

- Turncraft Architectural Wood Columns
- Poly-Classic® FRP Columns Vinyl Posts
- DuraStone<sup>™</sup> Columns
- DuraGlass Columns
- Craftsman Columns
- Wood Colonial Columns
- Poly-Classic® Railing System
- · Wood Porch Posts

Clicking on the product tab will pull up all the information available for that particular product.


#### ADDITIONAL INFORMATION


All of the information available in PDF format will be available here for your selection. Simply click on the desired PDF to view, save or print it out.

- Installation instructions
- Warranty information
- Specifications
- · Catalog PDF

#### **CAD DRAWINGS**

Turncraft's in-house CAD department can create detailed line drawings for your project.





#### **RESTORATION**

Turncraft is known for custom restoration projects. We can recreate products to match architecture of old with today's technology and materials.



Before



After



Before



After

SPECIAL CUSTOM ORDERS

Turncraft can manufacture custom Architectural wood columns and caps and bases to our customers specifications in various wood species.



www.Turncraft.com 49 |

# Quality at Every Zurn

#### AT TURNCRAFT THE QUALITY STARTS WITH THE MATERIALS.

As a division of Cascade Wood Products, we have direct control of the raw materials used in our wood products. Unlike other column manufacturers, our ability to monitor materials at each step of the process ensures every Turncraft wood column will offer both the natural beauty and the quality needed to stand the test of time. Quality control is further improved by using specialized machinery unique to each product line. By keeping our manufacturing facilities separate, we can better monitor, control and improve how well and how efficiently all of our products are constructed.



#### CREATING BEAUTY IS AN EXACTING PROCESS.

For Architectural Series columns, finger-jointed\* or solid staves are milled to required dimensions, assembled using the strongest Type-I waterproof glue, then metal-banded for curing. A computer-controlled lathe turns the assembled shaft to the precise taper desired, complete with true architectural entasis. The top is profiled, the entire column is machine sanded and flutes are milled at precise intervals and depths, ending in half-rounds at the top and bottom (except on Greek Doric).


#### ALTERNATIVE BUILDING MATERIALS

Turncraft has responded to the growing demand for alternative building materials. In 1994, we introduced our Poly-Classic\* line of fiberglass-reinforced polymer (FRP) columns to offer customers a more versatile and durable alternative. In 2005, we added the Poly-Classic\* Craftsman line—a popular design made of expanded cellular PVC for easy assembly and virtually maintenance-free performance.

#### **CUSTOM SOLUTIONS**

While Turncraft offers an extremely diverse lineup of products in more sizes and styles, we are also here to serve your imagination. With our access to the finest building materials, if you can dream it we can build it for you.

<sup>\*</sup> Using finger-jointed pieces conserves wood resources, reduces potential for warping and bow, and helps prevent checking or cracking of finished surfaces.



Computer-guided



























## Beauty. Value. Performance.

Turncraft's long history of high-quality craftsmanship is reflected in its entire product line, designed to add elegance and value to any building project.

Turncraft is your best source for:

- Turncraft Architectural Columns
- Poly-Classic® FRP Columns
- Poly-Classic® DuraStone™ Columns
- Poly-Classic® DuraGlass Columns
- Poly-Classic® Craftsman Series Columns
- Poly-Classic® Posts
- Poly-Classic® Composite Railing Systems
- Wood Colonial Columns
- Wood Porch

For detailed information on Turncraft's complete product line, please visit our website

www.Turncraft.com

PO Box 2429 White City, Oregon 97503 T 541 826 2911 F 541 826 1393 info@turncraft.com

distributed by:

©2013 Turncraft. All rights reserved. Turncraft and Poly-Classic are registered trademarks of Cascade Wood Products, Inc. Post Defense is a trademark of Cascade Wood Products, Inc. All other trademarks mentioned herein are the property of their respective owners. Information and specifications in this catalog are subject to change without notice.

